

## :: Slim Tape

special masking tape

### CHARACTERISTICS

CS Slim Tape is a special soft crepe masking tape that can withstand temperatures of up to 100°C. This high-quality product is designed for making extremely fine paint edge lines. Slim Tape has a very thin crepe paper backing and adheres extremely well to plastic parts and rubber seals.

Product advantages:

No adhesive residue

Extremely thin and smooth

Flexible and slightly extendable

Solvent-resistant and OK for wet sanding

Heat resistant to 100°C

### APPLICATION

High-quality masking tape for multi-color paint jobs, the painting of special designs, and masking plastic parts and rubber seals.

### PRODUCT DATA

MATERIAL DATA:

(Average values)

Backing material: Special soft crepe paper

Adhesive material: Acrylic

Total thickness: 0.09 mm

Adhesive power (N / 10 mm): 2.1574

Tensile strength (N /15 mm): 39.2266

Elongation at tear: 4.5 %



03/2016

Max. heat resistance: 100 °C

Dimensions:

Standard roll length: 50 m

Widths: 18 mm

### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE