

:: WR-Lifting Tape

masking tape with plastic strip

CHARACTERISTICS

WR Lifting Tape is a masking tape consisting of a crepe section and a high-strength, transparent plastic section. The two materials (crepe and plastic sections) are manufactured as one combination product. The adhesive on the crepe section is protected by masking paper to make masking jobs easier and protect the plastic film. This product is excellent for masking vehicles prior to the application of solvent-based or water-based paints and drying in a drying booth.

APPLICATION

Masking aid for masking difficult areas on the vehicle, especially seals (windows, doors, sunroofs, hoods, trunk lids, windshield and rear windows).

PRODUCT DATA

MATERIAL DATA:

(Average values)

Backing material: Lightly creped special paper

Edge material: Polyester film

Adhesive Material: Cross-linked modified rubber resin

Adhesive power (N / 25mm): 10

Tape thickness: 0.3 mm

Heat resistance (1h /°C): 120°C

Special properties: Stable when exposed to water-based paint

Color: Chamois

Core: diameter: 76 mm

Shelf life at 20°C: 12 months

Dimensions:



03/2016

Standard roll length: 10 m
Widths: 9, 18, 25 mm

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE