

:: Spotblender Spray

spot repair blender

CHARACTERISTICS

- Ideal for spot repair
- Blending of 2K Clear Coats as well as 2K topcoats
- Easy and quick application
- Very good solving properties
- Good polishing
- Reduces polishing work
- Achieves a homogeneous flow in the transition zones of topcoat or clear coat

APPLICATION

- Spot repair

PRODUCT DATA

Specific weight: 0.75 g/cm³

Shelf life: minimum 2 years

V.O.C.: < 820 g/l

Colour: transparent

HANDLING

SUBSTRATE:

- Apply immediately after the use of 2K High Speed Clear Coat or other 2K Clear Coats as well as 2K topcoat onto the transition zone of the surface to be blended.
- Sand surface in the transition zone with matt flex gold or gray in combination with Prep and Scuff or with sanding paper from P2000 to P4000.



06/2016

APPLICATION:

- Apply 2 – 3 light spray passes onto the transition zone of the 2K Clear Coat or 2K topcoat until a homogenous transition is obtained.
- No flash-off time required for the 2K Clear Coat or 2K topcoat.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Thin product contains isocyanate and can cause lung or breathing as well as hypersensitivity reaction. Before using or working with coatings material that contains isocyanate, all safety information's on the can label and the material safety data sheet must be read. Individuals with lung or breathing problems or prior reactions to isocyanate must not be exposed to vapour or spray mist.

The use of a respirator mask is necessary!

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Notice EU-safety data sheet as well as handling and warning notices on the label.



06/2016

Copyright VOSSCHEMIE