



1 Identification

- **Product identifier**
- **Trade name:** 02014-02164 Color Horizons Base Colors
- **Article number:**
02014, 02024, 02044, 02054, 02064, 02074, 02094, 02104, 02114, 02124, 02134, 02144, 02154, 02164
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

Sydney Automotive Paints and Equipment Pty Ltd
Unit 3A, 366 Edgar Street
Condell Park, 2200 NSW, Australia
02 9772 9000 FAX: 02 9772 9001
reception@sape.com.au
- **Further information obtainable from:**
cust_care@semproducts.com : SEM Products, Inc.: phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
(Contd. on page 2)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

xylene
Stoddard solvent
heptan-2-one
4-methylpentan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*
· **vPvB:** *Not applicable.*

3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description:** *Mixture: consisting of the following components.*

· **Dangerous components:**

123-86-4	<i>n-butyl acetate</i>	30-40%
	<i>Flam. Liq. 3, H226; STOT SE 3, H336</i>	
1330-20-7	<i>xylene</i>	10-13%
	<i>Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315</i>	
78-93-3	<i>butanone</i>	7-10%
	<i>Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336</i>	
110-43-0	<i>heptan-2-one</i>	7-10%
	<i>Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H332</i>	

(Contd. on page 3)



Trade name: 02014-02164 Color Horizons Base Colors

		(Contd. of page 2)
7429-90-5	aluminium ⚠️ Pyr. Sol. 1, H250; Water-react. 2, H261	7-10%
108-10-1	4-methylpentan-2-one ⚠️ Flam. Liq. 2, H225; ⚠️ Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	5-7%
108-88-3	toluene ⚠️ Flam. Liq. 2, H225; ⚠️ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠️ Skin Irrit. 2, H315; STOT SE 3, H336	1-1.5%
64742-95-6	Solvent naphtha (petroleum), light arom. ⚠️ Asp. Tox. 1, H304; ⚠️ Acute Tox. 4, H332; Flam. Liq. 4, H227	1-1.5%
8052-41-3	Stoddard solvent ⚠️ Flam. Liq. 3, H226; ⚠️ STOT RE 1, H372; Asp. Tox. 1, H304	1-1.5%
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate ⚠️ Skin Irrit. 2, H315; Skin Sens. 1, H317	≤1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** **Hazchem: ●3YE**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WES (Australia) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

1330-20-7 xylene

WES (Australia) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 350 mg/m³, 80 ppm

78-93-3 butanone

WES (Australia) Short-term value: 890 mg/m³, 300 ppm
Long-term value: 445 mg/m³, 150 ppm

110-43-0 heptan-2-one

WES (Australia) Long-term value: 233 mg/m³, 50 ppm

108-10-1 4-methylpentan-2-one

WES (Australia) Short-term value: 307 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

108-88-3 toluene

WES (Australia) Short-term value: 574 mg/m³, 150 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

8052-41-3 Stoddard solvent

WES (Australia) Long-term value: 790 mg/m³

(Contd. on page 5)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 4)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 79-80.5 °C

(Contd. on page 6)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 5)

· Flash point:	-8 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.957 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	68.6 %
VOC (EC)	656.3 g/l
Solids content:	31.4 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

AU
(Contd. on page 7)

Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 6)

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

AU


(Contd. on page 8)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 7)

14 Transport information

· UN-Number · ADG, IMDG, IATA	UN1263
· UN proper shipping name · ADG · IMDG, IATA	1263 PAINT, special provision 640D PAINT
· Transport hazard class(es) · ADG, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADG, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number: · Stowage Category	Warning: Flammable liquids. F-E, S-E B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II
· Hazchem:	● 3YE

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

123-86-4 | n-butyl acetate

(Contd. on page 9)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 8)

1330-20-7	xylene	
78-93-3	butanone	
110-43-0	heptan-2-one	
7429-90-5	aluminium	
108-10-1	4-methylpentan-2-one	
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	
108-88-3	toluene	
8052-41-3	Stoddard solvent	
1333-86-4	Carbon black	
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate	
111-76-2	2-butoxyethanol	
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate	
108-65-6	2-methoxy-1-methylethyl acetate	
100-41-4	ethylbenzene	
106-79-6	Dimethyl sebacate(Impurity)	
· Standard for the Uniform Scheduling of Medicines and Poisons		
1330-20-7	xylene	S6
78-93-3	butanone	S5
108-10-1	4-methylpentan-2-one	S5
108-88-3	toluene	S6
111-76-2	2-butoxyethanol	S6

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

xylene

Stoddard solvent

heptan-2-one

4-methylpentan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

(Contd. on page 10)



Trade name: 02014-02164 Color Horizons Base Colors

(Contd. of page 9)

P303+P361+P353 **IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gases.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

- **Department issuing SDS:** Environmental Protection Department

- **Contact:** 02 9772 9000

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

**Trade name: 02014-02164 Color Horizons Base Colors**

(Contd. of page 10)

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Pyr. Sol. 1: Pyrophoric solids – Category 1
Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

AU