
Technical Data Sheet

Ultimate Finish System™ Super Kut Compound is an aggressive compound that removes scratches and imperfections in difficult substrates and coatings. It produces a high gloss and shine on gel coat, hard-baked coatings, scratch resistant coatings, etc. Safe for use on all paints.

MIXING



Mix Ratio: Ready to Use
Pot Life: N/A

SURFACE PREPARATION



Wash surface to be sanded with soap and water.
Sand 1000 grit, wet or dry until imperfections or defects are removed. Finish sand with 1200-1500 grit.

APPLICATION



Do not apply in direct sunlight. Shake well before use. Wash and degrease surface to be compounded. Apply enough material to work a 2'x2' area. Using a Wool Compound Pad (5200 or 5260) or Orange Cutting Compound Pad (5272) on a mechanical buffer (1800 - 2200 rpm) begin working the material with moderate pressure. Keep buffer moving to prevent burn-through. To reduce sling, spread the material before buffing. Use additional applications as necessary. Continue with Tri-Cut II 5331/5334 or Cutting Compound 5361/5364 for a deep finish and shine.

PRODUCT SPECIFICATIONS

Color: White	Shelf Life: 1 year
Size: Gallon (5321), Quart (5324)	

REGULATORY

VOC Content: <17% by weight	Category: Automotive Rubbing or Polishing Compound
-----------------------------	--

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.