

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 1 of 12

## Caliper Paint Red

### SECTION 1: Identification

#### Product identifier

**Product name:** Caliper Paint Red

**Product code:** 42806



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Coating compound/ Surface coating/ paint

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**

**United States**

P.O.R. Products  
38 Portman Road  
New Rochelle, NY 10801  
914-636-0700

**Supplier:**

**Australia**

Sydney Automotive Paints & Equipment Pty Ltd  
A3 / 366 Edgar Street  
Condell Park, NSW 2200 Australia  
+61 2 9772 9000

#### Emergency telephone number:

**Australia**

**Emergency telephone AU Poison Information Centre 13 11 26**

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable liquids, category 3

Skin sensitization, category 1

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

H351 Suspected of causing cancer.

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 2 of 12

## Caliper Paint Red

- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use appropriate fire extinguishing methods for extinction.
- P321 Specific treatment (see first aid instructions on this label).
- P363 Wash contaminated clothing before reuse
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P314 Get medical advice/attention if you feel unwell
- P308+P313 If exposed or concerned: Get medical advice/attention
- P403+P235 Store in a well ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container according to local regulations.

**Hazards not otherwise classified:** None

### SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 8052-41-3	Stoddard Solvent	33-36
CAS number: 91-20-3	Naphthalene	<0.01
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	1-5
CAS number: 8030-76-0	Lecithins, soybean	0.1-0.5
CAS number: 112-34-5	2-(2-Butoxyethoxy)ethanol	0.01-0.05
CAS number: 1330-20-7	Xylene	0.01-0.05
CAS number: 100-41-4	Ethyl Benzene	<0.01

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 3 of 12

## Caliper Paint Red

CAS number: 22464-99-9	Zirconium 2-Ethylhexanoate	0.1-0.5
CAS number: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	0.05-0.1
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	0.1-0.5
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<3
CAS number: 1309-37-1	Diiron trioxide	<2
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.3
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.3

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 4 of 12

## Caliper Paint Red

### SECTION 5: Fire fighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

##### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

#### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: •3Y

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

#### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

#### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

#### Reference to other sections:

Not determined or not applicable.

### SECTION 7: Handling and storage precautions

#### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 5 of 12

## Caliper Paint Red

### Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.
- Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Stoddard Solvent	8052-41-3	Time weighted average: 790 mg/m <sup>3</sup>
	Naphthalene	91-20-3	Time Weighted Average: 52 mg/m <sup>3</sup> (10 ppm)
	Naphthalene	91-20-3	Short Term Exposure Limit: 79 mg/m <sup>3</sup> (15 ppm)
	Zirconium 2-Ethylhexanoate	22464-99-9	Time weighted average: 5 mg/m <sup>3</sup>
	Zirconium 2-Ethylhexanoate	22464-99-9	Short Term Exposure Limit: 10 mg/m <sup>3</sup>
	Diiron trioxide	1309-37-1	TWA: 5 mg/m <sup>3</sup>
	1-Methoxy-2-propanol acetate	108-65-6	TWA: 274 mg/m <sup>3</sup> (50 ppm); STEL: 548 mg/m <sup>3</sup> (100 ppm)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance. Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 6 of 12

## Caliper Paint Red

Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and at the end of work.  
Wash contaminated clothing before reuse.

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Red Colored Liquid
<b>Odor</b>	Solvent-like
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	>284°F (>140°C)
<b>Flash point (closed cup)</b>	>105°F (>41°C)
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	0.848-0.945 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not miscible.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Product is not self-igniting
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
<b>Oxidizing properties</b>	Not determined or not available.

#### Other information

<b>VOC Content</b>	60-68% (Max - < 430 g/L)
--------------------	--------------------------

### SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Can react violently with oxygen rich (oxidizing) materials.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 7 of 12

## Caliper Paint Red

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

### Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition.

Store away from oxidizing agents.

### Incompatible materials:

None known.

### Hazardous decomposition products:

CO, CO<sub>2</sub>.

Hydrocarbons.

## SECTION 11: Hazard information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h
Naphthalene	oral	LD50 - Mouse - 316 mg/kg
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.
Zirconium 2-Ethylhexanoate	Irritating to the skin.
Xylene	Irritating to the skin.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
2-(2-Butoxyethoxy)ethanol	Irritating effect on the eyes.
Methyl ethyl ketoxime	Risk of serious damage to the eyes.

### Respiratory or skin sensitization

**Assessment:** May cause an allergic skin reaction

#### Product data:

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 8 of 12

## Caliper Paint Red

No data available.

### Substance data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact

### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

### Substance data:

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Naphthalene	Not applicable.	Suspected of causing cancer.
Methyl ethyl ketoxime		May cause cancer.
Naphtha (petroleum), hydrodesulfurized heavy	Naphtha (petroleum), hydrodesulfurized heavy	Component may cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Stoddard Solvent	Group 3
Cobalt bis(2-ethylhexanoate)	Group 2B
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans
Naphthalene	Group 2B - Possibly carcinogenic to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Distillates (petroleum), hydrotreated light	Group 3 - Not classifiable as to its carcinogenicity to humans
Diiron trioxide	Group 3 - Not classifiable as to its carcinogenicity to humans

### National Toxicology Program (NTP):

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens
Naphthalene	Reasonably anticipated to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

### Substance data:

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Naphtha (petroleum), hydrodesulfurized heavy	May cause genetic defects.



# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 9 of 12

## Caliper Paint Red

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Ethyl Benzene	Repeated exposure damages the hearing organs.
Naphtha (petroleum), hydrodesulfurized heavy	Component affects the central nervous system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:**

No data available.

**Substance data:**

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Ethyl Benzene	May be fatal if swallowed and enters airway.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 10 of 12

## Caliper Paint Red

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Naphthalene	LC50 - Opossum Shrimp - 0.85 mg/L - 96 h
	LC50 - Melanotaenia fluviatilis (Crimson-Spotted Rainbowfish) - 0.213 mg/L - 96 h

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:**

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.



## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### Australian Dangerous Goods (ADG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3  
Packing group	III
Environmental hazards	Marine Pollutant (Stoddard Solvent)
Special precautions for user	None
Hazchem/Emergency Action Code	•3Y

### International Maritime Dangerous Goods (IMDG)



## Safety Data Sheet

According to the Australian Work Health and Safety Regulations



Initial preparation date: 04.24.2018

Page 11 of 12

### Caliper Paint Red

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	Paint	
<b>UN transport hazard class(es)</b>	3	 
<b>Packing group</b>	III	
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent)	
<b>Special precautions for user</b>	None	
<b>EmS number</b>	F-E, S-E	
<b>Stowage category</b>	A	
<b>Excepted quantities</b>	E1	
<b>Limited quantity</b>	5L	

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	Paint	
<b>UN transport hazard class(es)</b>	3	 
<b>Packing group</b>	III	
<b>Environmental hazards</b>	Marine Pollutant (Stoddard Solvent)	
<b>Special precautions for user</b>	None	
<b>ERG code</b>	3L	
<b>Excepted quantities</b>	E1	
<b>Passenger and cargo</b>	60L	
<b>Cargo aircraft only</b>	220L	
<b>Limited quantity</b>	10L	

### SECTION 15: Regulatory information

#### Australia regulations

##### Australian Inventory of Chemical Substances (AICS):

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
100-41-4	Ethyl Benzene	Listed
91-20-3	Naphthalene	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Listed
112-34-5	2-(2-Butoxyethoxy)ethanol	Listed
96-29-7	Methyl ethyl ketoxime	Listed
8030-76-0	Lecithins, soybean	Not Listed

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 12 of 12

## Caliper Paint Red

1330-20-7	Xylene	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed

### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
112-34-5	2-(2-Butoxyethoxy)ethanol	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-2-0

**HMIS:** 2-2-0

**Initial preparation date:** 04.24.2018

### Additional information:

Version 1.1

**End of Safety Data Sheet**