According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

SECTION 1: Identification

Product identifier Product name: 2K URETHANE GLOSS BLACK Product code: 43201, 43204, 43205, 43255

Recommended use of the product and restriction on use Relevant identified uses: Paint Uses advised against: Not determined or not applicable. Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: United States P.O.R. Products 38 Portman Road 914-636-0700

Supplier: Australia Sydney Automotive Paints & Equipment Pty Ltd A3 / 366 Edgar Street New Rochelle, NY 10801 Condell Park, NSW 2200 Australia +61 2 9772 9000

Emergency telephone number:

Australia

Emergency telephone AU Poison Information Centre 13 11 26

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST) Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3 Eye irritation, category 2A Skin irritation, category 2 Aspiration hazard, category 1 Specific target organ toxicity - single exposure, category 3, central nervous system Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.



According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/light/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash skin thoroughly after handling.

P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower.

P301+P310 If swallowed: Immediately call a poison center or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

P370+P378 In case of fire: Use agents recommended in section 5 for extinction.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse.

P302+P352 If on skin: Wash with soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P331 Do not induce vomiting.

P405 Store locked up.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents and container as instructed in Section 13.

Hazards not otherwise classified: None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 123-86-4	Acrylic Polyol	10-15
CAS number: 1330-20-7	Aromatic Hydrocarbon	10-15
CAS number: 98-56-6	Parachlorobenzotriflouride	5-10
CAS number: 100-41-4	Ethyl Benzene	<3
CAS number: 108-65-6	Pigment Dispersion	<2
CAS number: 77-58-7	Organic Tin Cmpd.	<0.01

Additional Information: None

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position Maintain an unobstructed airway Get medical advice/attention if you feel unwell

After skin contact:

Take off all contaminated clothing Gently blot or brush away excess product Wash with plenty of lukewarm, gently flowing water Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors Vapors can flow to distant ignition sources and flashback Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition Carbon monoxide and carbon dioxide may form upon combustion Heating causes a rise in pressure, risk of bursting and combustion Hazchem: •3Y

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation Ensure air handling systems are operational Wear protective eye wear, gloves and clothing Beware of vapors accumulating to form explosive concentrations Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing Use spark-proof tools and explosion-proof equipment Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders) Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation. Avoid breathing mist or vapor. Do not eat, drink, smoke or use personal products when handling chemical substances. Take precautionary measures against electrostatic discharges. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed. Protect from freezing and physical damage. Store in a cool, well-ventilated area. Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Acrylic Polyol	123-86-4	TWA: 713 mg/m ³ (150 ppm); STEL: 950 mg/m ³ (200 ppm)
	Aromatic Hydrocarbon	1330-20-7	TWA: 350 mg/m ³ (80 ppm) ; STEL: 655 mg/m ³ (150 ppm)
	Pigment Dispersion	108-65-6	TWA: 274 mg/m ³ (50 ppm); STEL: 548 mg/m ³ (100 ppm)
	Ethyl Benzene	100-41-4	TWA: 434 mg/m ³ (100 ppm); STEL: 543 mg/m ³ (125 ppm)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Black Liquid
Odor	Solvent
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	84°F (28.9°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.974-0.984 g/mL
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	500 сР - 600 сР
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Parachlorobenzotriflouride	Irritating to the skin.
Organic Tin Cmpd.	Corrosive to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Parachlorobenzotriflouride	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Organic Tin Cmpd.	Sensitization possible through skin contact.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Organic Tin Cmpd.	May cause mutagenic effects.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Name	Result
Organic Tin Cmpd.	May cause developmental toxicity.

Specific target organ toxicity (single exposure)

Assessment: May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Name	Result
Acrylic Polyol	SE May cause drowsiness or dizziness Central nervous system
Parachlorobenzotriflouride	Component affects the respiratory system.
Ethyl Benzene	Repeated exposure damages the hearing organs.
Organic Tin Cmpd.	Causes damage to organs through prolonged or repeated exposure - Thymus
	Causes damage to organs through single exposure - Thymus

Specific target organ toxicity (repeated exposure)

Assessment: May cause damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: May be fatal if swallowed and enters airways Product data: No data available. Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance	data:

Name	Result
Organic Tin Cmpd.	EC50 - Daphnia magna - 0.66 mg/L - 24 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

Substance data: No data available.

Bioaccumulative potential

Product data: No data available. **Substance data:** No data available.

Mobility in soil

Product data: No data available. **Substance data:** No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

UN number	1263
UN proper shipping name	PAINT
UN transport hazard class(es)	3
Packing group	111
Environmental hazards	None
Special precautions for user	None
Hazchem/Emergency Action Code	•3Y

International Maritime Dangerous Goods (IMDG)

UN number	1263	
UN proper shipping name	PAINT	
UN transport hazard class(es)	3	Hamane 3
Packing group		
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-E, S-E	
Excepted quantities	El	
Limited quantity	5L	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263
UN proper shipping name	PAINT

Page 9 of 11

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

UN transport hazard class(es)	3	
Packing group		
Environmental hazards	None	
Special precautions for user	None	
Excepted quantities	E1	
Limited quantity	10L	

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS):

	123-86-4	Acrylic Polyol	Listed	
	98-56-6	Parachlorobenzotriflouride	Listed	
	100-41-4	Ethyl Benzene	Listed	
	108-65-6	Pigment Dispersion	Listed	
	77-58-7	Organic Tin Cmpd.	Listed	
Sta	Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):			

1330-20-7	Aromatic Hydrocarbon	Listed

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-2-0

HMIS: 2-2-0

Initial preparation date: 10.23.2016

Additional information:

Version: 1.0

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.23.2016

2K URETHANE GLOSS BLACK

End of Safety Data Sheet

Page 11 of 11