

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 1 of 11

## High Temp Flat Black

### SECTION 1: Identification

#### Product identifier

**Product name:** High Temp Flat Black

**Product code:** 44101; 44104; 44105; 44116; 44155



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Paints and coatings

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**

**United States**

P.O.R. Products  
38 Portman Road  
New Rochelle, NY 10801  
914-636-0700

**Supplier:**

**Australia**

Sydney Automotive Paints & Equipment Pty Ltd  
A3 / 366 Edgar Street  
Condell Park, NSW 2200 Australia  
+61 2 9772 9000

#### Emergency telephone number:

**Australia**

**Emergency telephone AU Poison Information Centre 13 11 26**

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable liquids, category 3

Aspiration hazard, category 1

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 1A

#### Label elements

**Hazard pictograms:**



**Signal word:** Danger

#### Hazard statements:

H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H372 Causes damage to organs through prolonged or repeated exposure

H350 May cause cancer

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 2 of 11

## High Temp Flat Black

P240 Ground/bond container and receiving equipment  
P241 Use explosion-proof electrical/ventilating/light/equipment  
P242 Use only non-sparking tools  
P243 Take precautionary measures against static discharge  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P264 Wash skin thoroughly after handling  
P270 Do not eat, drink or smoke when using this product  
P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P281 Use personal protective equipment as required.  
P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower  
P370+P378 In case of fire: Use agents recommended in section 5 for extinction  
P331 Do not induce vomiting  
P301+P310 If swallowed: Immediately call a poison center or doctor/physician  
P308+P313 If exposed or concerned: Get medical advice/attention  
P314 Get medical advice/attention if you feel unwell  
P403+P235 Store in a well ventilated place. Keep cool  
P405 Store locked up  
P501 Dispose of contents and container as instructed in Section 13

**Hazards not otherwise classified:** None

## SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 75864-23-2	Iron Manganese Oxide	65-70
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	10-15
CAS number: 68953-58-2	Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	10-13
CAS number: 112-34-5	2-(2-Butoxyethoxy)ethanol	<0.01
CAS number: 8052-41-3	Stoddard Solvent	<3
CAS number: 1330-20-7	Xylene	<0.5
CAS number: 100-41-4	Ethyl Benzene	<0.5
CAS number: 22464-99-9	Zirconium 2-Ethylhexanoate	<0.5
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	<0.5

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 3 of 11

## High Temp Flat Black

CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<0.5
CAS number: 123-86-4	n-Butyl acetate	<0.5
CAS number: 14808-60-7	Silica, crystalline quartz	<0.5
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.5
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.5

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Fire fighting measures

### Extinguishing media

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 4 of 11

## High Temp Flat Black

### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: •3Y

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage precautions

### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 5 of 11

## High Temp Flat Black

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Xylene	1330-20-7	TWA: 350 mg/m <sup>3</sup> (80 ppm) ; STEL: 655 mg/m <sup>3</sup> (150 ppm)
	Ethyl Benzene	100-41-4	TWA: 434 mg/m <sup>3</sup> (100 ppm); STEL: 543 mg/m <sup>3</sup> (125 ppm)
	1-Methoxy-2-propanol acetate	108-65-6	TWA: 274 mg/m <sup>3</sup> (50 ppm); STEL: 548 mg/m <sup>3</sup> (100 ppm)
	n-Butyl acetate	123-86-4	TWA: 713 mg/m <sup>3</sup> (150 ppm); STEL: 950 mg/m <sup>3</sup> (200 ppm)
	Silica, crystalline quartz	14808-60-7	TWA: 0.1 mg/m <sup>3</sup> (Respirable dust)
	Stoddard Solvent	8052-41-3	TWA: 790 mg/m <sup>3</sup>

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 6 of 11

## High Temp Flat Black

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Flat Black Liquid
Odor	Characteristic
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	284°F (140°C)
Flash point (closed cup)	105°F (41°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	6.6 hPa
Vapor density	Not determined or not available.
Density	1.50 g/mL
Relative density	Not determined or not available.
Solubilities	Not miscible.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

#### Other information

VOC Content	565 (Calculated using US EPA Method 24A)
-------------	--

### SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

None under normal conditions of use and storage.

#### Conditions to avoid:

None known.

#### Incompatible materials:

None known.

#### Hazardous decomposition products:

None known.

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 7 of 11

## High Temp Flat Black

### SECTION 11: Hazard information

#### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h

#### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Xylene	Irritating to the skin.
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.
Zirconium 2-Ethylhexanoate	Irritating to the skin.

#### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
2-(2-Butoxyethoxy)ethanol	Irritating effect on the eyes.
Methyl ethyl ketoxime	Risk of serious damage to the eyes.

#### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.
Methyl ethyl ketoxime	May cause sensitization by skin contact

#### Carcinogenicity

**Assessment:** May cause cancer

**Product data:** No data available.

#### Substance data:

Name	Species	Result
------	---------	--------

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 8 of 11

## High Temp Flat Black

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Silica, crystalline quartz	Silica, crystalline quartz	Airborne particles of respirable size are known to cause cancer.
Methyl ethyl ketoxime		May cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Distillates (petroleum), hydrotreated light	Group 3 - Not classifiable as to its carcinogenicity to humans
Silica, crystalline quartz	Group 1 - Carcinogenic to humans

### National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz	Known to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Stoddard Solvent	May cause genetic defects.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Ethyl Benzene	Repeated exposure damages the hearing organs.
n-Butyl acetate	SE May cause drowsiness or dizziness. - Central nervous system
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Silica, crystalline quartz	Component affects the lungs through repeated exposure.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:**

No data available.

**Substance data:** No data available.



# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 9 of 11

## High Temp Flat Black

### Aspiration toxicity

**Assessment:** May be fatal if swallowed and enters airways

**Product data:**

No data available.

**Substance data:**

Name	Result
Ethyl Benzene	May be fatal if swallowed and enters airway.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airway.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations


Initial preparation date: 09.27.2017

Page 10 of 11


## High Temp Flat Black

### SECTION 14: Transport information


#### Australian Dangerous Goods (ADG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
Hazchem/Emergency Action Code	•3Y

#### International Maritime Dangerous Goods (IMDG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
EmS number	F-E, S-E
Stowage category	A
Excepted quantities	E1
Limited quantity	5L

#### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
ERG code	3L
Excepted quantities	E1
Passenger and cargo	60L
Cargo aircraft only	220L
Limited quantity	10L

### SECTION 15: Regulatory information

# Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.27.2017

Page 11 of 11

## High Temp Flat Black

### Australia regulations

#### Australian Inventory of Chemical Substances (AICS):

100-41-4	Ethyl Benzene	Listed
1330-20-7	Xylene	Listed
8052-41-3	Stoddard Solvent	Listed
75864-23-2	Iron Manganese Oxide	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed
123-86-4	n-Butyl acetate	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
14808-60-7	Silica, crystalline quartz	Listed
68953-58-2	Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
22464-99-9	Zirconium 2-Ethylhexanoate	Listed
112-34-5	2-(2-Butoxyethoxy)ethanol	Listed
96-29-7	Methyl ethyl ketoxime	Listed

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

1330-20-7	Xylene	Listed
136-52-7	Cobalt bis (2-ethylhexanoate)	Listed

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 3-2-0

**HMIS:** 3-2-0

**Initial preparation date:** 09.27.2017

### Additional information:

Version: 1.0

**End of Safety Data Sheet**