According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 1 of 12

## **Top Coat Gloss Black - Aerosol**

## **SECTION 1: Identification**

**Product identifier** 

Product name: Top Coat Gloss Black - Aerosol

**Product code: 45818** 

## Recommended use of the product and restriction on use

Relevant identified uses: Direct to metal rust preventive paint

Uses advised against: None Identified

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

Manufacturer: Supplier: United States Australia

P.O.R. Products Sydney Automotive Paints & Equipment Pty Ltd

38 Portman Road A3 / 366 Edgar Street

New Rochelle, NY 10801 Condell Park, NSW 2200 Australia

914-636-0700 +61 2 9772 9000

## **Emergency telephone number:**

**Australia** 

#### **Emergency telephone AU Poison Information Centre 13 11 26**

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST) Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

## SECTION 2: Hazard(s) identification

#### **GHS** classification:

Flammable aerosols, category 1

Compressed gases

Skin irritation, category 2

Eye irritation, category 2A

Skin sensitization, category 1

Carcinogenicity, category 2

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 1

#### Label elements

#### **Hazard pictograms:**









Signal word: Danger

## **Hazard statements:**

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation



According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 2 of 12

## **Top Coat Gloss Black - Aerosol**

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

H336 May cause drowsiness or dizziness

H372 Causes damage to organs through prolonged or repeated exposure

H315+H320 Causes skin and eye irritation.

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P211 Do not spray on an open flame or other ignition source

P251 Pressurized container. Do not pierce or burn, even after use

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P272 Contaminated work clothing should not be allowed out of the workplace

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P281 Use personal protective equipment as required.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 If on skin: Wash with soap and water

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P308+P313 If exposed or concerned: Get medical advice/attention

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Call a poison center or doctor/physician if you feel unwell

P332+P313 If skin irritation occurs: Get medical advice/attention

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists get medical advice/attention

P363 Wash contaminated clothing before reuse

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 Get medical advice/attention if you feel unwell

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P410+P403 Protect from sunlight. Store in a well ventilated place

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents and container as instructed in Section 13

#### Hazards not otherwise classified: None

#### **SECTION 3: Composition and information on ingredients**

Identification	Name	Weight %
CAS number: 67-64-1	Acetone	10-30

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 3 of 12

## **Top Coat Gloss Black - Aerosol**

CAS number: 74-98-6	Propane	10-30
CAS number: 540-88-5	T-Butyl Acetate	10-30
CAS number: 64742-89-8	Vm&P Naphtha	10-30
CAS number: 64742-48-9	Hydrotreated Heavy Petroleum Naphtha	5-10
CAS number: 1333-86-4	Carbon Black	1-5
CAS number: 64742-88-7	Mineral Spirits	1-5
CAS number: 1330-20-7	Xylene	1-5
CAS number: 100-41-4	Ethyl Benzene	0.1-1

Additional Information: None

#### **SECTION 4: First aid measures**

#### **Description of first aid measures**

#### **General notes:**

Get medical attention if you feel unwell

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

## After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

#### Most important symptoms and effects, both acute and delayed

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 4 of 12

## **Top Coat Gloss Black - Aerosol**

#### Acute symptoms and effects:

Not determined or not applicable.

#### **Delayed symptoms and effects:**

Not determined or not applicable.

#### Immediate medical attention and special treatment

#### **Specific treatment:**

Not determined or not applicable.

#### Notes for the doctor:

Treat symptomatically

#### **SECTION 5: Fire fighting measures**

### **Extinguishing media**

#### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Contents under pressure

In a fire or if heated, a pressure increase will occur and the container may burst or explode

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

#### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: na

## **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

#### **Environmental precautions:**

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

#### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceus earth (clay), acid binders, universal

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 5 of 12

## **Top Coat Gloss Black - Aerosol**

binders)

Dispose of contents / container in accordance with local regulations

#### Reference to other sections:

Not determined or not applicable.

## **SECTION 7: Handling and storage precautions**

### Precautions for safe handling:

KEEP OUT OF REACH OF CHILDREN.

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

#### Conditions for safe storage, including any incompatibilities:

Protect from freezing and physical damage.

Protect from direct sunlight.

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## **SECTION 8: Exposure controls and personal protection**

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Carbon Black	1333-86-4	TWA: 3 mg/m³
	Xylene	1330-20-7	TWA: 350 mg/m³ (80 ppm); STEL: 655 mg/m³ (150 ppm)
	Ethyl Benzene	100-41-4	TWA: 434 mg/m³ (100 ppm); STEL: 543 mg/m³ (125 ppm)
	Acetone	67-64-1	TWA: 1185 mg/m³ (500 ppm); STEL: 2375 mg/m³ (1000 ppm)
	T-Butyl Acetate	540-88-5	TWA: 950 mg/m³ (200 ppm)

#### **Biological limit values:**

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

## Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 6 of 12

## **Top Coat Gloss Black - Aerosol**

#### Personal protection equipment

## Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

## Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### **Respiratory protection:**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

#### **General hygienic measures:**

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance   Black Pressurized Product	
Odor	Paint-like
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	> 95.30 °C
Initial boiling point/range	> 56.10 °C
Flash point (closed cup)	> -17.00 °C (Liquid); -104.40 °C (Propellant)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Extremely Flammable Aerosol
Upper flammability/explosive limit	13.0%
Lower flammability/explosive limit	0.70%
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.732 g/cm <sup>3</sup>
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	229.40 °C
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

#### Other information

Percent VOC	48.71 % wt
Percent Volatile	83.64 % wt

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 7 of 12

## Top Coat Gloss Black - Aerosol

Percent HAP	2.05 % wt
Global Warming Potential	0.91 GWP
Ozone Depletion Potential	0.00 ODP
HAP Content	15.01 g/L (0.13 lbs/gal)
VOC Regulatory/Actual	624.92 g/L (5.21 lbs/gal) / 356.57 g/L (2.98 lbs/gal)
Maximum Incremental Reactivity	0.7170 g O3/g

## SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

#### **Chemical stability:**

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

#### **Conditions to avoid:**

Keep away from heat, sparks and flames.

#### Incompatible materials:

Strong Oxidizing Agents, Strong Acids.

## **Hazardous decomposition products:**

Acetic Acid

#### **SECTION 11: Hazard information**

#### **Acute toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

Product data: No data available.

**Substance data:** 

Name	Route	Result
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h

### Skin corrosion/irritation

**Assessment:** Causes skin irritation

**Product data:** No data available.

#### **Substance data:**

Name	Result
Hydrotreated Heavy Petroleum Naphtha	Irritating to the skin.
Xylene	Irritating to the skin.

## Serious eye damage/irritation

Assessment: Causes serious eye irritation

**Product data:** 

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 8 of 12

## **Top Coat Gloss Black - Aerosol**

No data available.

#### **Substance data:**

Name	Result
Acetone	Causes serious eye irritation.

#### Respiratory or skin sensitization

**Assessment:** May cause an allergic skin reaction

**Product data:**No data available.

Substance data: No data available.

Carcinogenicity

**Assessment:** Suspected of causing cancer

Product data: No data available.

Substance data:

Name	Species	Result
Vm&P Naphtha	Solvent naphtha (petroleum), light aliphatic	The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).
Carbon Black	Carbon Black	The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black.

## International Agency for Research on Cancer (IARC):

Name	Classification
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Carbon Black	Group 2B - Possibly carcinogenic to humans
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans

**National Toxicology Program (NTP):** None of the ingredients are listed.

## Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

Product data:
No data available.
Substance data:

Name	Result
	The classification as a mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

## Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

# Specific target organ toxicity (single exposure)

**Assessment:** May cause drowsiness or dizziness

Product data: No data available. Substance data:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 9 of 12

## **Top Coat Gloss Black - Aerosol**

Name	Result
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.
Hydrotreated Heavy Petroleum Naphtha	Component affects the central nervous system.
Mineral Spirits	Component affects the central nervous system after repeated exposure.
Ethyl Benzene	Repeated exposure damages the hearing organs.

#### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:**No data available.

Substance data: No data available.

#### **Aspiration toxicity**

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Hydrotreated Heavy Petroleum Naphtha	May be fatal if swallowed and enters airway.
Ethyl Benzene	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

#### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

#### Other information:

No data available.

## **SECTION 12: Ecological information**

## Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

**Product data:** No data available. **Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available. **Substance data:** No data available.

#### **Bioaccumulative potential**

**Product data:** No data available. **Substance data:** No data available.

#### Mobility in soil

Generated by SDSPublisher (patent-pending) www.GSMSDS.com, 1-813-435-5161

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 10 of 12

## **Top Coat Gloss Black - Aerosol**

Product data: No data available.
Substance data: No data available.
Other adverse effects: No data available.

## **SECTION 13: Disposal considerations**

### **Disposal methods:**

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

# **SECTION 14: Transport information**

## **Australian Dangerous Goods (ADG)**

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1
Packing group	None
Environmental hazards	None
Special precautions for user	None
Hazchem/Emergency Action Code	na

## **International Maritime Dangerous Goods (IMDG)**

UN number	1950
UN proper shipping name	Aerosols, Limited Quantity
UN transport hazard class(es)	2.1
Packing group	None
Environmental hazards	None
Special precautions for user	None
EmS number	F-D, S-U
Stowage category	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacityabove 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.
Excepted quantities	E0

## International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 11 of 12

## **Top Coat Gloss Black - Aerosol**

UN transport hazard class(es)	2.1	Land Land Land Land Land Land Land Land
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
ERG code	10L	
Excepted quantities	E0	
Passenger and cargo	75 kg	
Cargo aircraft only	150 kg	
Limited quantity	30 kg G	

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code		
Bulk Name	None	
Ship type	None	
Pollution category	None	

## **SECTION 15: Regulatory information**

#### **Australia regulations**

## Australian Inventory of Chemical Substances (AICS):

74-98-6	Propane	Listed
67-64-1	Acetone	Listed
540-88-5	T-Butyl Acetate	Listed
64742-89-8	Vm&P Naphtha	Listed
64742-48-9	Hydrotreated Heavy Petroleum Naphtha	Listed
64742-88-7	Mineral Spirits	Listed
1330-20-7	Xylene	Listed
1333-86-4	Carbon Black	Listed
100-41-4	Ethyl Benzene	Listed

## Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

	Xylene	Listed
67-64-1	Acetone	Listed

## **SECTION 16: Other information**

## **Abbreviations and Acronyms: None**

## **Disclaimer:**

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information

According to the Australian Work Health and Safety Regulations

Initial preparation date: 09.26.2017 Page 12 of 12

## Top Coat Gloss Black - Aerosol

relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-4-3 **HMIS:** 2-4-3

Initial preparation date: 09.26.2017

**Additional information:** 

Version: 1.0

**End of Safety Data Sheet**