according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BPO-Härter rot

Product code : 132.413

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

stance/Mixture

: Curing chemical

1.3 Details of the supplier of the safety data sheet

Company : A.Förster & Co.KG

Esinger Steinweg 50 25436 Uetersen

Germany

info@foerster-co.de

Telephone : 04122-3682

Responsible Department : Laboratory

04122-3682

info@foerster-co.de

1.4 Emergency telephone number

Telephone : POISONS INFORMATION CENTRE

Australia

13 11 26

1.5 Details of the supplier/importer

Company : Sydney Automotive Paints and Equipment

Unit A3, 366 Edgar Street

Condell Park, 2200

reception@sape.com.au

Telephone : 02 9772 9000 Telefax : 02 9772 9001

Responsible Department : Marketing

02 9772 9000

according to Regulation (EC) No. 1907/2006



### **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E H242: Heating may cause a fire.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Short-term (acute) aquatic hazard, Cate-

gory 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Cat-

egory 1

H410: Very toxic to aquatic life with long lasting

effects.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Warning

Hazard statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances

/combustible materials.

P234 Keep only in original packaging.P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

sent and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P410 Protect from sunlight.

## Disposal:

P501 Dispose of contents/container to an approved facility in

accordance with local, regional, national and interna-

tional regulations.

Hazardous components which must be listed on the label: dibenzoyl peroxide

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Mixture

contains

Organic Peroxide

# Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M factor (acute) = 10 M factor (chronic) = 10	>= 45 - < 55
ethanediol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373	>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



Hazchem: 1W

# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

Move out of dangerous area.

Take off contaminated clothing and shoes immediately. Show this safety data sheet to the doctor in attendance.

First aider needs to protect himself.

If inhaled : Move to fresh air.

Get medical attention.

In case of skin contact : Wash off immediately with soap and plenty of water.

Call a physician if irritation persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Keep eye wide open while rinsing.

Remove contact lenses. Consult a physician.

If swallowed : Rinse mouth with water.

Do NOT induce vomiting. Call a physician immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Dry powder Water spray jet

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Hazardous decomposition products formed under fire condi-

tions.

according to Regulation (EC) No. 1907/2006



### **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019 1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus and protective suit.

Further information Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Wear personal protective equipment.

Evacuate personnel to safe areas.

Ensure adequate ventilation, especially in confined areas.

Remove all sources of ignition.

Do not smoke.

Avoid contact with skin, eyes and clothing.

In the case of vapour formation use a respirator with an ap-

proved filter.

#### 6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Do not flush with water.

#### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures Ensure that eyewash stations and safety showers are close to

the workstation location.

Advice on safe handling Use only with adequate ventilation.

Provide sufficient air exchange and/or exhaust in work rooms.

Wear personal protective equipment.

Keep away from heat and sources of ignition.

Handle and open container with care. Keep container tightly closed and dry.

Never return unused material to storage receptacle.

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

Risk of decomposition.

Prevent contamination with readily oxidizable materials and

polymerisation accelerators. Avoid inhalation of vapour or mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid release to the environment.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Keep away from open flames, hot surfaces and sources of

ignition.

Keep away from direct sunlight. Avoid shock and friction.

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container.

Avoid letting the product become dry.

Keep containers tightly closed in a cool, well-ventilated place. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

Advice on common storage

Keep away from food, drink and animal feedingstuffs.

Keep away from reducing agents. Incompatible with acids and bases.

Heavy metal compounds

Recommended storage tem-

perature

<= 25 °C

7.3 Specific end use(s)

Specific use(s) : No data available

The rules which cover amongst other things the requirement for ventilation, protective clothing, personal protective equipment etc. can be obtained from the National Occupational

Health and Safety Board.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
- Components	07101101	of exposure)	Common parameters	240.0
dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the			
	long-term exposure limit should be used.			
dimethyl phthalate	131-11-3	TWA	5 mg/m3	GB EH40
		STEL	10 mg/m3	GB EH40
ethanediol	107-21-1	STEL	40 ppm	2000/39/EC

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

1	1	•	1	1
			104 mg/m3	
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm	2000/39/EC
			52 mg/m3	
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA (Vapour)	20 ppm	GB EH40
			52 mg/m3	
Further information	Can be absorbed through the skin. The assigned substances are those for			
	which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA (particles)	10 mg/m3	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for			
	which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL (Vapour)	40 ppm	GB EH40
			104 mg/m3	
Further information	Can be absorbed through the skin. The assigned substances are those for			
	which there are concerns that dermal absorption will lead to systemic toxicity.			

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	• •	•	• •	
Substance name	End Use	Exposure routes	Potential health effects	Value
dibenzoyl peroxide	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13.3 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	39 mg/m3
ethanediol	Workers	Inhalation	Long-term local ef- fects	35 mg/m3
	Workers	Dermal	Long-term systemic effects	106 mg/kg
	Consumers	Inhalation	Long-term local ef- fects	7 mg/m3
	Consumers	Dermal	Long-term systemic effects	53 mg/kg

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0.00002 mg/l
	Intermittent use/release	0.000602 mg/l
	Marine water	0.000002 mg/l
	Fresh water sediment	0.0127 mg/kg dry weight (d.w.)
	Marine sediment	0.00127 mg/kg dry weight (d.w.)
	Soil	0.0025 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.35 mg/l
ethanediol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Sewage treatment plant	199.5 mg/l
	Fresh water sediment	37 mg/kg
	Marine sediment	3.7 mg/kg

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

### 8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Neoprene gloves

Material : Nitrile rubber

Break through time : > 30 min

Glove thickness : >= 0.14 mm

Directive : DIN EN 374

Protective index : Class 2

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough.

The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protec-

tive glove.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

or heat-resistant synthetic fibres.

Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational

exposure limits.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

In case of inadequate ventilation wear respiratory protection.

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : When using do not eat, drink or smoke.

Ensure that eye flushing systems and safety showers are

located close to the working place. Avoid contact with the skin and the eyes. Use only with adequate ventilation.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

Appearance : paste

Colour : red

Odour : characteristic

Melting point/range : not determined

Boiling point/boiling range : not determined

Flash point : Not applicable, Decomposition

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower :

flammability limit

not determined

Vapour pressure : not determined

Density : 1.15 - 1.25 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, kinematic : not determined

Oxidizing properties : Organic peroxide

Sustains combustion

9.2 Other information

Self-Accelerating decomposi: :

tion temperature (SADT)

50 °C

Peroxide content : 50 %

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No decomposition if used as directed.

# 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Risk of decomposition.

Reacts violently in contact with acids, amines, driers, polymer-

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

isation accelerators and easily oxidized materials.

10.4 Conditions to avoid

Conditions to avoid : Do not expose to temperatures above: > 25 °C

Extremes of temperature and direct sunlight.

Keep away from heat and sources of ignition.

Contact with incompatible substances can cause decomposi-

tion at or below SADT.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

#### 10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.

### **Components:**

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 24.3 mg/l

Exposure time: 4 h

ethanediol:

Acute oral toxicity : Acute toxicity estimate: 500.0 mg/kg

Method: Converted acute toxicity point estimate

Acute inhalation toxicity : LC50 (Rat): > 2.5 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Mouse): > 3,500 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

### **Components:**

### ethanediol:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

## **Aspiration toxicity**

Not classified based on available information.

## **Components:**

### ethanediol:

No aspiration toxicity classification

## **SECTION 12: Ecological information**

### 12.1 Toxicity

## **Components:**

### dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Fish): 0.0316 mg/l Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0.0711

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02

mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10: 0.001 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

ethanediol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 72,860 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : NOEC (algae): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 15,380 mg/l Exposure time: 28 d

Species: Fish

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 1,000 mg/l Exposure time: 23 d

Species: Daphnia magna (Water flea)

### 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

### **Product:**

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

**Product:** 

Additional ecological infor-

mation

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not mix waste streams during collection.

Do not dispose of with domestic refuse.

Do not empty into drains, dispose of this material and its con-

tainer at hazardous or special waste collection point. Dispose of in accordance with local regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:

16 05 06, laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chem-

icals

16 09 03, peroxides, for example hydrogen peroxide

# **SECTION 14: Transport information**

## 14.1 UN number

ADN : UN 3108
ADR : UN 3108
RID : UN 3108
IMDG : UN 3108
IATA : UN 3108

14.2 UN proper shipping name

**ADN** : ORGANIC PEROXIDE TYPE E, SOLID

(dibenzoyl peroxide)

**ADR** : ORGANIC PEROXIDE TYPE E, SOLID

(dibenzoyl peroxide)

RID : ORGANIC PEROXIDE TYPE E, SOLID

(dibenzoyl peroxide)

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

**IMDG** : ORGANIC PEROXIDE TYPE E, SOLID

(dibenzoyl peroxide)

IATA : Organic peroxide type E, solid

(dibenzoyl peroxide)

14.3 Transport hazard class(es)

ADN : 5.2
ADR : 5.2
RID : 5.2
IMDG : 5.2
IATA : 5.2

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2

**ADR** 

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : P1 Hazard Identification Number : 539 Labels : 5.2

**IMDG** 

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo : 570

aircraft)

Packing group : Not assigned by regulation

Labels : Division 5.2 - Organic peroxides, Handling Label - Keep Away

From Heat

IATA (Passenger)

Packing instruction (passen: 570

ger aircraft)

Packing group : Not assigned by regulation

Labels : Division 5.2 - Organic peroxides, Handling Label - Keep Away

From Heat

14.5 Environmental hazards

ADN

Environmentally hazardous : no

according to Regulation (EC) No. 1907/2006



### **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : yes Hazchem: 1W

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P6b SELF-REACTIVE

SUBSTANCES AND

MIXTURES and ORGANIC

**PEROXIDES** 

E1 ENVIRONMENTAL

**HAZARDS** 

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H241 : Heating may cause a fire or explosion.

H302 : Harmful if swallowed.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Org. Perox. : Organic peroxides
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008: CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not

according to Regulation (EC) No. 1907/2006



# **BPO-Härter rot**

Version Revision Date: Date of last issue: 05.04.2019
1.1 GB/EN 29.10.2019 Date of first issue: 05.04.2019

Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

# Classification of the mixture: Classification procedure:

Org. Perox. E	H242	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.