



## 1 Identification

· **Product identifier**

· **Trade name:** 39143 Trim Black

· **Article number:** 39143

· **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

Sydney Automotive Paints and Equipment Pty Ltd

Unit 3A, 366 Edgar Street

Condell Park, 2200 NSW, Australia

02 9772 9000 FAX: 02 9772 9001

reception@sape.com.au

· **Further information obtainable from:**

cust\_care@semproducts.com : SEM Products, Inc.: phone 1-800-831- 1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** Poison Information Centre Call 13 11 26 (Australia)

## 2 Hazard(s) Identification

· **Classification of the substance or mixture**



flame

Aerosol 1 H222 Extremely flammable aerosol.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)



**Trade name: 39143 Trim Black**

(Contd. of page 1)

· **Hazard pictograms**



GHS02   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

*toluene*  
*xylene*

· **Hazard statements**

*H222 Extremely flammable aerosol.*  
*H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H361 Suspected of damaging fertility or the unborn child.*  
*H336 May cause drowsiness or dizziness.*  
*H373 May cause damage to organs through prolonged or repeated exposure.*  
*H304 May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.*  
*P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*  
*P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*P405 Store locked up.*  
*P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*  
*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

67-64-1	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	30-40%
68476-86-8	Petroleum gases, liquefied, sweetened ⚠ Flam. Gas 1, H220; ⚠ Press. Gas C, H280	13-30%
108-88-3	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	13-30%
110-19-0	isobutyl acetate ⚠ Flam. Liq. 2, H225	7-10%

(Contd. on page 3)



**Trade name: 39143 Trim Black**

		(Contd. of page 2)
1330-20-7	xylene	1.5-5%
	⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
78-93-3	butanone	1.5-5%
	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	
123-86-4	n-butyl acetate	1-1.5%
	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire Fighting Measures

- **Extinguishing media** **Hazchem: 2YE**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** No special measures required.

(Contd. on page 4)



**Trade name: 39143 Trim Black**

(Contd. of page 3)

- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

<b>67-64-1 acetone</b>	
WES (Australia)	Short-term value: 2375 mg/m <sup>3</sup> , 1000 ppm Long-term value: 1185 mg/m <sup>3</sup> , 500 ppm
<b>108-88-3 toluene</b>	
WES (Australia)	Short-term value: 574 mg/m <sup>3</sup> , 150 ppm Long-term value: 191 mg/m <sup>3</sup> , 50 ppm Sk
<b>110-19-0 isobutyl acetate</b>	
WES (Australia)	Long-term value: 713 mg/m <sup>3</sup> , 150 ppm
<b>1330-20-7 xylene</b>	
WES (Australia)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 350 mg/m <sup>3</sup> , 80 ppm
<b>78-93-3 butanone</b>	
WES (Australia)	Short-term value: 890 mg/m <sup>3</sup> , 300 ppm Long-term value: 445 mg/m <sup>3</sup> , 150 ppm
<b>123-86-4 n-butyl acetate</b>	
WES (Australia)	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 713 mg/m <sup>3</sup> , 150 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

(Contd. on page 5)



**Trade name: 39143 Trim Black**

(Contd. of page 4)

· **Respiratory protection:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

· **Protection of hands:**

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**

*Safety glasses*



Tightly sealed goggles

## 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Aerosol

**Colour:** Black

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 405 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 6)



**Trade name: 39143 Trim Black**

(Contd. of page 5)

· <b>Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapour pressure at 20 °C:</b>	233 hPa
· <b>Density at 20 °C:</b>	0.74751 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	92.0 %
<b>Water:</b>	0.0 %
<b>VOC (EC)</b>	687.9 g/l
<b>Solids content:</b>	7.9 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

· <b>LD/LC50 values relevant for classification:</b>		
<b>108-88-3 toluene</b>		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

(Contd. on page 7)



**Trade name: 39143 Trim Black**

(Contd. of page 6)

- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**  
Repr. 2

## 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |                                  |                     |
|----------------------------------|---------------------|
| · <b>UN-Number</b>               |                     |
| · <b>ADG, IMDG, IATA</b>         | UN1950              |
| · <b>UN proper shipping name</b> |                     |
| · <b>ADG</b>                     | 1950 AEROSOLS       |
| · <b>IMDG</b>                    | AEROSOLS            |
| · <b>IATA</b>                    | AEROSOLS, flammable |

(Contd. on page 8)

Trade name: 39143 Trim Black

(Contd. of page 7)

· **Transport hazard class(es)**

· **ADG**



· **Class** 2 5F Gases.  
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
· **Label** 2.1

· **Packing group**  
· **ADG, IMDG, IATA** Void

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases.  
· **EMS Number:** F-D,S-U  
· **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre:  
Category A. For AEROSOLS with a capacity above 1 litre:  
Category B. For WASTE AEROSOLS: Category C, Clear of  
living quarters.  
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1  
except for division 1.4. For AEROSOLS with a capacity  
above 1 litre: Segregation as for the appropriate  
subdivision of class 2. For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of Marpol  
and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADG**  
· **Limited quantities (LQ)** 1L  
· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity  
· **Transport category** 2  
· **Tunnel restriction code** D

· **IMDG**  
· **Limited quantities (LQ)** 1L  
· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

(Contd. on page 9)





**Trade name: 39143 Trim Black**

(Contd. of page 8)

· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1
· <b>Hazchem:</b>	2YE

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Chemical Substances**

67-64-1	acetone	
68476-86-8	Petroleum gases, liquefied, sweetened	
108-88-3	toluene	
110-19-0	isobutyl acetate	
1330-20-7	xylene	
78-93-3	butanone	
123-86-4	n-butyl acetate	
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	
1333-86-4	Carbon black	
68611-44-9	Modified Silica	
111-76-2	2-butoxyethanol	
68855-54-9	diatomaceous earth	
9002-88-4	Polyethylene low density	
67-56-1	methanol	
100-41-4	ethylbenzene	
7732-18-5	water	
· <b>Standard for the Uniform Scheduling of Medicines and Poisons</b>		
67-64-1	acetone	S5
108-88-3	toluene	S6
1330-20-7	xylene	S6
78-93-3	butanone	S5
111-76-2	2-butoxyethanol	S6
67-56-1	methanol	S5, S6

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

toluene

xylene

· **Hazard statements**

H222 Extremely flammable aerosol.

(Contd. on page 10)

AU



**Trade name: 39143 Trim Black**

(Contd. of page 9)

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H361 Suspected of damaging fertility or the unborn child.*

*H336 May cause drowsiness or dizziness.*

*H373 May cause damage to organs through prolonged or repeated exposure.*

*H304 May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.*

*P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*

*P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P405 Store locked up.*

*P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a** FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

*H220 Extremely flammable gas.*

*H225 Highly flammable liquid and vapour.*

*H226 Flammable liquid and vapour.*

*H280 Contains gas under pressure; may explode if heated.*

*H304 May be fatal if swallowed and enters airways.*

*H312 Harmful in contact with skin.*

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H332 Harmful if inhaled.*

*H336 May cause drowsiness or dizziness.*

*H361 Suspected of damaging fertility or the unborn child.*

*H373 May cause damage to organs through prolonged or repeated exposure.*

· **Department issuing SDS:** Environmental Protection Department

· **Contact:** 02 9772 9000

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

(Contd. on page 11)

**Trade name: 39143 Trim Black**

(Contd. of page 10)

*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*Flam. Gas 1: Flammable gases – Category 1*  
*Aerosol 1: Aerosols – Category 1*  
*Press. Gas C: Gases under pressure – Compressed gas*  
*Flam. Liq. 2: Flammable liquids – Category 2*  
*Flam. Liq. 3: Flammable liquids – Category 3*  
*Acute Tox. 4: Acute toxicity – Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*  
*Repr. 2: Reproductive toxicity – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*  
*Asp. Tox. 1: Aspiration hazard – Category 1*

AU