Version number 10

Printing date 03.10.2017



Revision: 03.10.2017

Page 1/10

1 Identification

- · Product identifier
- · Trade name: <u>39803 Clear Chip Guard</u>
- Article number: 39803
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225 Sydney Automotive Paints and Equipment Pty Ltd

Unit 3A, 366 Edgar Street Condell Park, 2200 NSW, Australia 02 9772 9000 FAX: 02 9772 9001 reception@sape.com.au

• Further information obtainable from:

- cust_care@semproducts.com : SEM Products,Inc.: phone 1-800-831-1122, M TH 7am 4pm EDT
- Emergency telephone number: Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

· Classification of the substance or mixture



Aerosol 1

H222 Extremely flammable aerosol.



Repr. 2 H361 Suspected of damaging fertility or the unborn child. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · Label elements

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). (Contd. on page 2)

Page 2/10

Safety Data Sheet according to WHS Regulations

Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

SEM

Trade name: 39803 Clear Chip Guard

11	(Contd. of page
Hazard pictogra	ms
	\mathbf{A}
<u>< () > ()</u>	
GHS02 GHS	07 GHS08
Signal word Dar	nger
Hazard-determi	ning components of labelling:
toluene	
Hazard statemen	nts
H222 Extremely	flammable aerosol.
H315 Causes ski	n irritation.
H319 Causes ser	ious eye irritation.
H361 Suspected	of damaging fertility or the unborn child.
H336 May cause	drowsiness or dizziness.
H373 May cause	damage to organs through prolonged or repeated exposure.
	al if swallowed and enters airways.
Precautionary st	atements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}C/122$ $^{\circ}F$.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
Other hazards	
Results of PBT a	und vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

• Description: Mixture: consisting of the following components.

108-88-3	toluene	30-40%
	� Flam. Liq. 2, H225; � Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; � Skin Irrit. 2, H315; STOT SE 3, H336	
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
	🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	
67-64-1	acetone	13-30%
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2A, H319; STOT SE 3, H336	
78-93-3	butanone	5-7%
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2A, H319; STOT SE 3, H336	
2807-30-9	2-(propyloxy)ethanol	1.5-5%
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Eye Irrit. 2A, H319	

Page 3/10

Safety Data Sheet according to WHS Regulations

Revision: 03.10.2017

(Contd. of page 2)

1.5-5%

Printing date 03.10.2017

Version number 10

Trade name: 39803 Clear Chip Guard

NJ TSRN: 8009285004 Polyester Plasticizer

🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H319

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· Description of first aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Hazchem: 2YE

Page 4/10

Safety Data Sheet according to WHS Regulations

Revision: 03.10.2017

Printing date 03.10.2017

Version number 10

Trade name: 39803 Clear Chip Guard

(Contd. of page 3)

- \cdot Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WES (Australia) Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm Sk

67-64-1 acetone

WES (Australia) Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm

78-93-3 butanone

WES (Australia) Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

SEM

Trade name: 39803 Clear Chip Guard

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• *Eye protection:* Safety glasses

Tightly sealed goggles

Information on basic physical and chem	nical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 55 ℃
Flash point:	-103 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	465 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	233 hPa
Density at 20 °C:	0.75288 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. of page 4)

Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

Trade name: 39803 Clear Chip Guard

	(Contd. c	of page 5
· Solvent content:		
Organic solvents:	86.3 %	
VOC(EC)	649.8 g/l	
Solids content:	13.7 %	
• Other information	No further relevant information available.	

10 Stability and Reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

108-88-3 toluene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

· Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2

12 Ecological Information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)



Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

Trade name: 39803 Clear Chip Guard

· Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- \cdot Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

UN-Number		
ADG, IMDG, IATA	UN1950	
UN proper shipping name		
ADG	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
Transport hazard class(es)		
ADG		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
*		
Class	2.1	
Label	2.1	
Packing group		
ADG, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	

(Contd. of page 6)

Page 8/10

Safety Data Sheet according to WHS Regulations

Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

Trade name: 39803 Clear Chip Guard

	(Contd. of page
Special precautions for user	Warning: Gases.
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capacit
	above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS
	Subalvision of class 2. For wASIE AEROSOLS Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex I	
and the IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1
Hazchem:	2YE

15 Regulatory information

Australian	Inventory of Chemical Substances	
108-88-	3 toluene	
68476-86-	8 Petroleum gases, liquefied, sweetened	
67-64-	1 acetone	
78-93-	3 butanone	
2807-30-	9 2-(propyloxy)ethanol	
Standard j	for the Uniform Scheduling of Medicines and Poisons	
108-88-3	toluene	Se
67-64-1	acetone	S
78-9 <i>3-3</i>	butanone	St
GHS labe	lelements The product is classified and labelled according to the Globally Harmonis	sed System (GHS) (Contd. on page

SEM

Page 9/10

Safety Data Sheet according to WHS Regulations

Printing date 03.10.2017

Version number 10

Revision: 03.10.2017

Trade name: 39803 Clear Chip Guard

· Hazard pictogra	(Contd. of page 8)
GHS02 GH	507 GHS08
· Signal word Da	inger
· Hazard-determ	ining components of labelling:
toluene	
• Hazard stateme	nts
•	y flammable aerosol.
H315 Causes sk	in irritation.
	rious eye irritation.
	l of damaging fertility or the unborn child.
	e drowsiness or dizziness.
	e damage to organs through prolonged or repeated exposure.
• •	tal if swallowed and enters airways.
· Precautionary	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
<i>P305+P351+P</i> .	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}C/122$ $^{\circ}F$.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Seveso category	18/EU Dus substances - ANNEX I None of the ingredients is listed. P 3a FLAMMABLE AEROSOLS ntity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)

Version number 10

Page 10/10

Revision: 03.10.2017

Printing date 03.10.2017

Trade name: 39803 Clear Chip Guard

	(Contd. of page 9)
Department issuing SDS: Environmental Protection Department	
Contact: 02 9772 9000	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulat. International Transport of Dangerous Goods by Rail)	ions Concerning the
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concern.	ing the International
Carriage of Dangerous Goods by Road)	ing the International
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas C: Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	