

## :: Topline WP S

230 x 280 mm

### CHARACTERISTICS

- Excellent flexibility of soaked material. Extended soaking is no longer necessary.
- By using the product under wet conditions premature loading can be prevented, thus leading to a long life.
- No dust development.
- Perfect surfaces.

### APPLICATION

Sanding of primer, putty, filler and lacquer.

### PRODUCT DATA

Base stock: Flexible latex A-paper and strong latex C-paper with high tear resistance

Bonding: Resin over resin, waterproof

Grain Type: Silicon Carbide

Coating: Close

Grain Size: P 80 - P 2000

Base stock A = P 2000 - P 220

Base stock C = P 1200 - P 60

### SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions.

In practice, the materials, surfaces or site conditions are so different



03/2016

that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE