

GYSPOT 2600

GYSPOT 2600, with its 2600 A maximum output current, is the ideal product for dent pulling and straightening of low thickness car body elements (hood, door, roof panel). The product is multifunctional, which makes it a complete solution. Thanks to its low power consumption, it can work on a simple 230V power supply.

A MULTIFUNCTIONAL DENT PULLER

3 modes available:

- **Welding of stars or washers** for car body element pulling.
- **Welding of wavy wire**, ideal to follow a curved profile. (e.g. wheelhouse)
- **Contact shrinking**, to work on light impacts and for good finishing.


EASY TO USE

- **Intuitive**, the potentiometer allows to select both the output power and the requested mode.
- **Automatic**, the welding is generated by simply making a contact between the tool and the element to straighten.









Delivered as a standard with :

- 1 spot inertia hammer (1,1kg) and 1 star holder tip
- 3 stars
- 1 contact shrinking tip
- 1 earth pad



Spot 800 trolley (optional)
Réf: 051331



		I_{RMS}	$I_{2 MAX}$	U_2 		AUTO MATIC detection		
230V 50/60Hz	16	1800	2600	5,4	OK	•	20x18x32	14,1

Other characteristics :

- Cable lengths
Earth: 1,7 m
Gun: 2 m
Power cord: 2 m

Phone: (02) 9772 9000

<https://shop.sape.com.au/products/GYS2600>



SAPE
GROUP