

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 1 of 14

Engine Enamel BLACK

SECTION 1: Identification

Product identifier

Product name: Engine Enamel BLACK

Product code: 42038



Recommended use of the product and restriction on use

Relevant identified uses: Coating compound/ Surface coating/ paint

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products
38 Portman Road
New Rochelle, NY 10801
914-636-0700

Supplier:

Australia

Sydney Automotive Paints & Equipment Pty Ltd
A3 / 366 Edgar Street
Condell Park, NSW 2200 Australia
+61 2 9772 9000

Emergency telephone number:

Australia

Emergency telephone AU Poison Information Centre 13 11 26

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin sensitization, category 1

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

Reproductive toxicity, category 2

Acute aquatic hazard, category 3

Chronic aquatic hazard, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H315+H320 Causes skin and eye irritation.

H317 May cause an allergic skin reaction.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 2 of 14

Engine Enamel BLACK

H372 Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure. (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H351 Suspected of causing cancer. (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H361 Suspected of damaging fertility or the unborn child. (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash ... thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

P273 Avoid release to the environment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use ... for extinction.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P321 Specific treatment (see ... on this label).

P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P362+P364 Take off contaminated clothing and wash it before reuse.

P314 Get medical advice/attention if you feel unwell

P308+P313 If exposed or concerned: Get medical advice/attention

P391 Collect spillage

P403+P235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to ...

Hazards not otherwise classified: None

SECTION 3: Composition and information on ingredients

| Identification | Name | Weight % |
|----------------|------|----------|
|----------------|------|----------|

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 3 of 14

Engine Enamel BLACK

| | | |
|---------------------------|----------------------------------------------|-----------|
| CAS number: 8052-41-3 | Stoddard Solvent | 33-38 |
| CAS number: 91-20-3 | Naphthalene | <0.01 |
| CAS number: 556-67-2 | Octamethylcyclotetrasiloxane | 2-5 |
| CAS number: 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy | 0.01-0.1 |
| CAS number: 1333-86-4 | Carbon Black | 1-3 |
| CAS number: 1330-20-7 | Xylene | 0.1-0.5 |
| CAS number: 100-41-4 | Ethyl Benzene | 0.01-0.1 |
| CAS number: 8001-26-1 | Linseed Oil | 0.1-1 |
| CAS number: 64742-95-6 | Solvent naphtha (petroleum), light arom. | 0.01-0.05 |
| CAS number: 22464-99-9 | Zirconium 2-Ethylhexanoate | 0.1-0.5 |
| CAS number: 64742-47-8 | Distillates (petroleum), hydrotreated light | 0.1-0.5 |
| CAS number: 68424-45-3 | Fatty acids, linseed-oil | 0.01-0.05 |
| CAS number: 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 1-3 |
| CAS number: 8030-76-0 | Lecithins, soybean | 0.1-0.3 |
| CAS number: 71-43-2 | Benzene | <0.01 |
| CAS number: 112-34-5 | 2-(2-Butoxyethoxy)ethanol | 0.01-0.05 |
| CAS number: 136-52-7 | Cobalt bis(2-ethylhexanoate) | <0.3 |
| CAS number: 66071-03-2 | Linseed oil, polymerized, oxidized | 0.05-0.1 |
| CAS number: 108-88-3 | Toluene | <0.01 |
| CAS number: 96-29-7 | Methyl ethyl ketoxime | <0.3 |

Additional Information: None

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 4 of 14

Engine Enamel BLACK

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 5 of 14

Engine Enamel BLACK

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: •3Y

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|------------------|------------|----------------------------------------------|
| Australia | Stoddard Solvent | 8052-41-3 | Time weighted average: 790 mg/m ³ |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 6 of 14

Engine Enamel BLACK

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|----------------------------|------------|----------------------------------------------------------|
| | Naphthalene | 91-20-3 | Time Weighted Average: 52 mg/m ³ (10 ppm) |
| | Naphthalene | 91-20-3 | Short Term Exposure Limit: 79 mg/m ³ (15 ppm) |
| | Zirconium 2-Ethylhexanoate | 22464-99-9 | Time weighted average: 5 mg/m ³ |
| | Zirconium 2-Ethylhexanoate | 22464-99-9 | Short Term Exposure Limit: 10 mg/m ³ |
| | Carbon Black | 1333-86-4 | TWA: 3 mg/m ³ |

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

| | |
|------------------------------|----------------------------------|
| Appearance | Black Colored Liquid |
| Odor | Solvent-like |
| Odor threshold | Not determined or not available. |
| pH | Not determined or not available. |
| Melting point/freezing point | Not determined or not available. |
| Initial boiling point/range | >284°F (>140°C) |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 7 of 14

Engine Enamel BLACK

| | |
|-----------------------------------------|---------------------------------------------------------------------------------------------|
| Flash point (closed cup) | >105°F (>41°C) |
| Evaporation rate | Not determined or not available. |
| Flammability (solid, gas) | Not determined or not available. |
| Upper flammability/explosive limit | Not determined or not available. |
| Lower flammability/explosive limit | Not determined or not available. |
| Vapor pressure | Not determined or not available. |
| Vapor density | Not determined or not available. |
| Density | 0.848-0.945 g/cm ³ |
| Relative density | Not determined or not available. |
| Solubilities | Not miscible. |
| Partition coefficient (n-octanol/water) | Not determined or not available. |
| Auto/Self-ignition temperature | Product is not self-igniting |
| Decomposition temperature | Not determined or not available. |
| Dynamic viscosity | Not determined or not available. |
| Kinematic viscosity | Not determined or not available. |
| Explosive properties | Product is not explosive . However, formation of explosive air/vapor mixtures are possible. |
| Oxidizing properties | Not determined or not available. |

Other information

| | |
|-------------|--------------------------|
| VOC Content | 60-68% (Max - < 430 g/L) |
|-------------|--------------------------|

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Can react violently with oxygen rich (oxidizing) materials.

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition.

Store away from oxidizing agents.

Incompatible materials:

CO, CO₂.

Hydrocarbons.

Hazardous decomposition products:

None known.

SECTION 11: Hazard information

Acute toxicity

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 8 of 14

Engine Enamel BLACK

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

| Name | Route | Result |
|---------------|------------|----------------------------|
| Xylene | dermal | LD50 - Rat - > 1,700 mg/kg |
| | inhalation | LC50 - Rat - 5,000 ppm/4 h |
| Ethyl Benzene | inhalation | LCLo - Rat - 4,000 ppm/4 h |
| Naphthalene | oral | LD50 - Mouse - 316 mg/kg |

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

| Name | Result |
|-----------------------------------------|-------------------------|
| Xylene | Irritating to the skin. |
| Cobalt bis(2-ethylhexanoate) | Irritating to the skin. |
| Zirconium 2-Ethylhexanoate | Irritating to the skin. |
| Naphtha (petroleum), hydrotreated heavy | Irritating to the skin. |
| Benzene | Irritating to the skin. |
| Toluene | Irritating to the skin. |

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

| Name | Result |
|---------------------------|-------------------------------------|
| 2-(2-Butoxyethoxy)ethanol | Irritating effect on the eyes. |
| Methyl ethyl ketoxime | Risk of serious damage to the eyes. |
| Linseed Oil | Not Irritating to the eyes |
| Benzene | Irritating effect on the eyes. |

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

| Name | Result |
|------------------------------|------------------------------------------|
| Cobalt bis(2-ethylhexanoate) | May cause sensitization by skin contact. |
| Methyl ethyl ketoxime | May cause sensitization by skin contact |

Carcinogenicity

Assessment: Suspected of causing cancer

Product data: No data available.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 9 of 14

Engine Enamel BLACK

Substance data:

| Name | Species | Result |
|----------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stoddard Solvent | Stoddard Solvent | Component may cause cancer. |
| Naphthalene | Not applicable. | Suspected of causing cancer. |
| Methyl ethyl ketoxime | | May cause cancer. |
| Naphtha (petroleum), hydrodesulfurized heavy | Naphtha (petroleum), hydrodesulfurized heavy | Component may cause cancer. |
| Carbon Black | Carbon Black | The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black. |
| Naphtha (petroleum), hydrotreated heavy | | May cause cancer. |
| Solvent naphtha (petroleum), light arom. | Solvent naphtha (petroleum), light arom. | Component may cause cancer. |
| Benzene | Benzene | Confirmed human carcinogen. |

International Agency for Research on Cancer (IARC):

| Name | Classification |
|---------------------------------------------|----------------------------------------------------------------|
| Stoddard Solvent | Group 3 |
| Xylene | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Ethyl Benzene | Group 2B - Possibly carcinogenic to humans |
| Cobalt bis(2-ethylhexanoate) | Group 2B |
| Naphthalene | Group 2B - Possibly carcinogenic to humans |
| Distillates (petroleum), hydrotreated light | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Carbon Black | Group 2B - Possibly carcinogenic to humans |
| Benzene | Group 1 - Carcinogenic to humans |
| Toluene | Group 3 - Not classifiable as to its carcinogenicity to humans |

National Toxicology Program (NTP):

| Name | Classification |
|------------------------------|------------------------------------------------|
| Cobalt bis(2-ethylhexanoate) | Reasonably anticipated to be human carcinogens |
| Naphthalene | Reasonably anticipated to be human carcinogens |
| Benzene | Known to be human carcinogens |

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

| Name | Result |
|----------------------------------------------|----------------------------|
| Stoddard Solvent | May cause genetic defects. |
| Naphtha (petroleum), hydrodesulfurized heavy | May cause genetic defects. |
| Naphtha (petroleum), hydrotreated heavy | May cause genetic defects. |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 10 of 14

Engine Enamel BLACK

| Name | Result |
|------------------------------------------|----------------------------|
| Solvent naphtha (petroleum), light arom. | May cause genetic defects. |
| Benzene | May cause genetic defects. |

Reproductive toxicity

Assessment: Suspected of damaging fertility or the unborn child

Product data:

No data available.

Substance data:

| Name | Result |
|------------------------------|------------------------------------------------------|
| Octamethylcyclotetrasiloxane | Suspected human reproductive toxicant. |
| Toluene | Suspected of damaging fertility or the unborn child. |

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

| Name | Result |
|----------------------------------------------|---------------------------------------------------------------------|
| Ethyl Benzene | Repeated exposure damages the hearing organs. |
| Naphtha (petroleum), hydrodesulfurized heavy | Component affects the central nervous system. |
| Naphtha (petroleum), hydrotreated heavy | Component affects the central nervous system. |
| Benzene | Causes damage to the organs through prolonged or repeated exposure. |
| Toluene | Component affects the central nervous system. |

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data:

| Name | Result |
|------------------|-----------------------------------------------------------------|
| Stoddard Solvent | Causes damage to organs through prolonged or repeated exposure. |

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

| Name | Result |
|---------------------------------------------|-----------------------------------------------|
| Stoddard Solvent | May be fatal if swallowed and enters airways. |
| Ethyl Benzene | May be fatal if swallowed and enters airway. |
| Distillates (petroleum), hydrotreated light | May be fatal if swallowed and enters airway. |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 11 of 14

Engine Enamel BLACK

| Name | Result |
|------------------------------------------|----------------------------------------------|
| Naphtha (petroleum), hydrotreated heavy | May be fatal if swallowed and enters airway. |
| Solvent naphtha (petroleum), light arom. | May be fatal if swallowed and enters airway. |

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Harmful to aquatic life

Product data: No data available.

Substance data:

| Name | Result |
|-------------|-----------------------------------------------------------------------------------|
| Naphthalene | LC50 - Opossum Shrimp - 0.85 mg/L - 96 h |
| | LC50 - Melanotaenia fluviatilis (Crimson-Spotted Rainbowfish) - 0.213 mg/L - 96 h |

Chronic (long-term) toxicity

Product data: No data available.

Substance data:

| Name | Result |
|------------------------------|-----------------------------------------------|
| Cobalt bis(2-ethylhexanoate) | NOEC - Pimephales promelas - 0.21 mg/L - 34 d |

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Safety Data Sheet



According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018



Page 12 of 14

Engine Enamel BLACK



Australian Dangerous Goods (ADG)

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3   |
| Packing group | III |
| Environmental hazards | Marine Pollutant (Stoddard Solvent) |
| Special precautions for user | None |
| Hazchem/Emergency Action Code | •3Y |

International Maritime Dangerous Goods (IMDG)

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3   |
| Packing group | III |
| Environmental hazards | Marine Pollutant (Stoddard Solvent) |
| Special precautions for user | None |
| EmS number | F-E, S-E |
| Stowage category | A |
| Excepted quantities | E1 |
| Limited quantity | 5L |

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3   |
| Packing group | III |
| Environmental hazards | Marine Pollutant (Stoddard Solvent) |
| Special precautions for user | None |
| ERG code | 3L |
| Excepted quantities | E1 |
| Passenger and cargo | 60L |
| Cargo aircraft only | 220L |
| Limited quantity | 10L |

SECTION 15: Regulatory information

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 13 of 14

Engine Enamel BLACK

Australia regulations

Australian Inventory of Chemical Substances (AICS):

| | | |
|------------|----------------------------------------------|------------|
| 8052-41-3 | Stoddard Solvent | Listed |
| 1330-20-7 | Xylene | Listed |
| 100-41-4 | Ethyl Benzene | Listed |
| 136-52-7 | Cobalt bis(2-ethylhexanoate) | Listed |
| 91-20-3 | Naphthalene | Listed |
| 22464-99-9 | Zirconium 2-Ethylhexanoate | Listed |
| 112-34-5 | 2-(2-Butoxyethoxy)ethanol | Listed |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | Listed |
| 96-29-7 | Methyl ethyl ketoxime | Listed |
| 68424-45-3 | Fatty acids, linseed-oil | Listed |
| 8001-26-1 | Linseed Oil | Listed |
| 66071-03-2 | Linseed oil, polymerized, oxidized | Listed |
| 556-67-2 | Octamethylcyclotetrasiloxane | Listed |
| 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy | Listed |
| 1333-86-4 | Carbon Black | Listed |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | Listed |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | Listed |
| 71-43-2 | Benzene | Listed |
| 108-88-3 | Toluene | Listed |
| 8030-76-0 | Lecithins, soybean | Not Listed |

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

| | | |
|------------|---------------------------------------------|--------|
| 8052-41-3 | Stoddard Solvent | Listed |
| 112-34-5 | 2-(2-Butoxyethoxy)ethanol | Listed |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | Listed |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | Listed |
| 108-88-3 | Toluene | Listed |

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-2-0

HMIS: 2-2-0

Initial preparation date: 04.24.2018

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 14 of 14

Engine Enamel BLACK

Additional information:

Version 1.1

End of Safety Data Sheet