According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 1 of 11

Rubberized Under Coating - Aerosol

SECTION 1: Identification

Product identifier

Product name: Rubberized Under Coating - Aerosol

Product code: 49308

PRODUCTS

Recommended use of the product and restriction on use

Relevant identified uses: Underbody coating

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: Supplier: United States Australia

P.O.R. Products Sydney Automotive Paints & Equipment Pty Ltd

38 Portman Road A3 / 366 Edgar Street

New Rochelle, NY 10801 Condell Park, NSW 2200 Australia

914-636-0700 +61 2 9772 9000

Emergency telephone number:

Australia

Emergency telephone AU Poison Information Centre 13 11 26

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

GHS classification:

Flammable aerosols, category 1

Compressed gases

Skin irritation, category 2

Eye irritation, category 2A

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard pictograms:









Signal word: Danger

Hazard statements:

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation

H319 Causes serious eye irritation

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 2 of 11

Rubberized Under Coating - Aerosol

H361 Suspected of damaging fertility or the unborn child

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure

H315+H320 Causes skin and eye irritation.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P211 Do not spray on an open flame or other ignition source

P251 Pressurized container. Do not pierce or burn, even after use

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P281 Use personal protective equipment as required.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 If on skin: Wash with soap and water

P332+P313 If skin irritation occurs: Get medical advice/attention

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P308+P313 If exposed or concerned: Get medical advice/attention

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists get medical advice/attention

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 Get medical advice/attention if you feel unwell

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P410+P403 Protect from sunlight. Store in a well ventilated place

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents and container as instructed in Section 13

Hazards not otherwise classified: None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 79-20-9	Methyl acetate	10-30
CAS number: 74-98-6	Propane	10-30
CAS number: 108-88-3	Toluene	10-30
CAS number: 540-88-5	T-Butyl Acetate	10-30

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 3 of 11

Rubberized Under Coating - Aerosol

CAS number:	Acetone	5-10
67-64-1		

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 4 of 11

Rubberized Under Coating - Aerosol

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Contents under pressure

In a fire or if heated, a pressure increase will occur and the container may burst or explode

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: na

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceus earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

Conditions for safe storage, including any incompatibilities:

Protect from freezing and physical damage.

Protect from direct sunlight.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 5 of 11

Rubberized Under Coating - Aerosol

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Toluene	108-88-3	TWA: 191 mg/m³ (50 ppm) ; STEL: 574 mg/m³ (150 ppm)
	T-Butyl Acetate	540-88-5	TWA: 950 mg/m³ (200 ppm)
	Methyl acetate	79-20-9	TWA 8-hr: 606 mg/m³ (200 ppm); STEL 15-min: 757 mg/m³ (250 ppm)
	Acetone	67-64-1	TWA: 1185 mg/m³ (500 ppm); STEL: 2375 mg/m³ (1000 ppm)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Initial preparation date: 10.30.2017 Page 6 of 11

Rubberized Under Coating - Aerosol

Information on basic physical and chemical properties

	1
Appearance	Black Pressurized Product
Odor	Paint-like
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	> 57.00 °C
Flash point (closed cup)	> -20.00 °C (Liquid); -104.40 °C (Propellant)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Extremely Flammable Aerosol
Upper flammability/explosive limit	16.0 Vol %
Lower flammability/explosive limit	1.5 Vol %
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.793 g/cm³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	354.00 °C
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

<u> </u>		
Percent Volatile	83.20 % wt	
Percent VOC	42.15 % wt	
Percent HAP	17.18 % wt	
Global Warming Potential	1.16 GWP	
Ozone Depletion Potential	0.00 ODP	
VOC Regulatory/Actual	632.41 g/L (5.28 lbs/gal) / 334.24 g/L (2.79 lbs/gal)	
HAP Content	136.24 g/L (1.14 lbs/gal)	
Maximum Incremental Reactivity	0.9450 g O3/g	

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 7 of 11

Rubberized Under Coating - Aerosol

Conditions to avoid:

Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

Incompatible materials:

Strong Oxidizing Agents, Strong Acids, Potassium t-Butoxide.

Hazardous decomposition products:

Methanol, Acetic Acid.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:
No data available.
Substance data:

Name	Result
Toluene	Irritating to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:
No data available.

Substance data:

Name	Result
Methyl acetate	Irritating to the eyes.
Acetone	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. **Substance data:** No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Toluene	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 8 of 11

Rubberized Under Coating - Aerosol

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Suspected of damaging fertility or the unborn child

Product data:
No data available.
Substance data:

Name	Result
Toluene	Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure)

Assessment: May cause drowsiness or dizziness

Product data: No data available. Substance data:

Name	Result
Toluene	Component affects the central nervous system.
Methyl acetate	May cause drowsiness or dizziness through single exposure.
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: May cause damage to organs through prolonged or repeated exposure

Product data:No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. **Substance data:** No data available.

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 9 of 11

Rubberized Under Coating - Aerosol

Persistence and degradability

Product data: No data available. **Substance data:** No data available.

Bioaccumulative potential

Product data: No data available. **Substance data:** No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

UN number	1950	
UN proper shipping name	Aerosols, flammable, Limited Quantity	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
Hazchem/Emergency Action Code	na	

International Maritime Dangerous Goods (IMDG)

UN number	1950	
UN proper shipping name	Aerosols, Limited Quantity	
UN transport hazard class(es)	2.1	
Packing group	None	
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-D, S-U	
Stowage category	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacityabove 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.	

Generated by SDSPublisher (patent-pending) www.GSMSDS.com, 1-813-435-5161

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 10 of 11

Rubberized Under Coating - Aerosol

Excepted quantities	F0
zxceptea qualitities	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1
	P. AAMHULE CAS
Packing group	None
Environmental hazards	None
Special precautions for user	None
ERG code	10L
Excepted quantities	E0
Passenger and cargo	75 kg
Cargo aircraft only	150 kg
Limited quantity	30 kg G

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS):

540-88-5	T-Butyl Acetate	Listed
74-98-6	Propane	Listed
108-88-3	Toluene	Listed
79-20-9	Methyl acetate	Listed
67-64-1	Acetone	Listed

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

108-88-3	Toluene	Listed
67-64-1	Acetone	Listed

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-4-3 **HMIS:** 2-4-3

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.30.2017 Page 11 of 11

Rubberized Under Coating - Aerosol

Initial preparation date: 10.30.2017

Additional information:

Version: 1.0

End of Safety Data Sheet