SEM

Printing date 03.10.2017 Version

Version number 9 Revision: 03.10.2017

1 Identification

- · Product identifier
- · Trade name: 13000 Series Color Coat Clears RTS
- · Article number: 13001, 13004, 13006, 13011, 13014, 13016, 13021, 13024, 13026
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

Sydney Automotive Paints and Equipment Pty Ltd Unit 3A, 366 Edgar Street Condell Park, 2200 NSW, Australia 02 9772 9000 FAX: 02 9772 9001 reception@sape.com.au

- · Further information obtainable from:
- cust_care@semproducts.com: SEM Products,Inc.: phone 1-800-831-1122, M TH 7am 4pm EDT
- · Emergency telephone number: Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

· Classification of the substance or mixture



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

 (Contd. on page 2)

ΑI

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 1)

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling: toluene
- · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210 P241 *Use explosion-proof electrical/ventilating/lighting equipment.*

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT:

vinyl resin

· vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture: consisting of the following components.

108-88-3	toluene	60-70%	
	♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Skin Irrit. 2, H315; STOT SE 3, H336		
78-93-3	butanone	13-30%	
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2A, H319; STOT SE 3, H336		
	vinyl resin	1.5-5%	
	PBT		
2807-30-9	2-(propyloxy)ethanol	1.5-5%	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Eye Irrit. 2A, H319		
108-65-6	2-methoxy-1-methylethyl acetate	1.5-5%	
	♦ Flam. Liq. 3, H226		

(Contd. on page 3)

SEM

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 2)

Hazchem: •3YE

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

SEM

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WES (Australia) Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm

78-93-3 butanone

WES (Australia) Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WES (Australia) Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

SEM

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

0 Dh	vaigal	and	CI	remical	D	won.	aution
J I II	ysicui	unu	\cup_{I}	<i>temicui</i>	Щ	עעט	erues

· Information on ba	isic pnysicai ai	na cnemicai j	properues
Con and Informat	ion		

· General Information

 \cdot Appearance:

Form: Liquid

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

 $\cdot \textit{Change in condition}$

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 79 °C

· Flash point: -4 °C

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 514 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 11.5 Vol %

· Vapour pressure at 20 °C: 105 hPa

Density at 20 °C: 0.89154 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)

SEM

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

	(0)	Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	87.4 %	
VOC (EC)	779.5 g/l	
Solids content:	8.5 %	
· Other information	No further relevant information available.	

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eve damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

SEM

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 6)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

 $Do \ not \ allow \ product \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT:

vinyl resin

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADG, IMDG, IATA	UN1263
UN proper shipping name	
ADG	1263 PAINT, special provision 640D
IMDG, IATA	PAINT
Transport hazard class(es)	
ADG, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADG, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Annex II	I of Marpol
and the IBC Code	Not applicable.

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

	(Contd. of page 7)
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II
· Hazchem:	•3YE

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian	Inventory of Chemical Substances	
108-88-3	toluene	
78-93-3	B butanone	
	vinyl resin	
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	
2807-30-9	2-(propyloxy)ethanol	
108-65-6	2-methoxy-1-methylethyl acetate	
71-36-3	B butan-1-ol	
· Standard fo	or the Uniform Scheduling of Medicines and Poisons	
108-88-3 t	oluene	<i>S6</i>
78-93-3 l	putanone	<i>S5</i>
71-36-3 l	putan-1-ol	S5, S6

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: toluene
- · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 9)

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 8)

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Environmental Protection Department
- · Contact: 02 9772 9000
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

(Contd. on page 10)

Printing date 03.10.2017 Version number 9 Revision: 03.10.2017

Trade name: 13000 Series Color Coat Clears RTS

(Contd. of page 9)

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.