



1 Identification

· **Product identifier**

· **Trade name:** 62243 EZCoat Gray

· **Article number:** 62243

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

Sydney Automotive Paints and Equipment Pty Ltd

Unit 3A, 366 Edgar Street

Condell Park, 2200 NSW, Australia

02 9772 9000 FAX: 02 9772 9001

reception@sape.com.au

· **Further information obtainable from:**

cust_care@semproducts.com : SEM Products, Inc.: phone 1-800-831- 1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

· **Classification of the substance or mixture**



flame

Aerosol 1 H222 Extremely flammable aerosol.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

Trade name: 62243 EZCoat Gray

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

toluene

· **Hazard statements**

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.





· **vPvB:** Not applicable.

3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

67-64-1	acetone	40-60%
		
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
		
108-88-3	toluene	7-10%
		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5-5%
		
110-19-0	isobutyl acetate	1.5-5%
		
78-93-3	butanone	1.5-5%
		
763-69-9	ethyl 3-ethoxypropionate	1-1.5%
		

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

AU

(Contd. on page 3)



Trade name: 62243 EZCoat Gray

(Contd. of page 2)

4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

Hazchem: 2YE

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.

(Contd. on page 4)



Trade name: 62243 EZCoat Gray

(Contd. of page 3)

- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WES (Australia)	Short-term value: 2375 mg/m ³ , 1000 ppm Long-term value: 1185 mg/m ³ , 500 ppm
-----------------	--

108-88-3 toluene

WES (Australia)	Short-term value: 574 mg/m ³ , 150 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----------------	--

110-19-0 isobutyl acetate

WES (Australia)	Long-term value: 713 mg/m ³ , 150 ppm
-----------------	--

78-93-3 butanone

WES (Australia)	Short-term value: 890 mg/m ³ , 300 ppm Long-term value: 445 mg/m ³ , 150 ppm
-----------------	---

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.

- **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Trade name: 62243 EZCoat Gray

(Contd. of page 4)

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 55.8-56.6 °C

· **Flash point:**

-103 °C

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

465 °C

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:

1.9 Vol %

Upper:

13 Vol %

· **Vapour pressure at 20 °C:**

233 hPa

· **Density at 20 °C:**

0.75265 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not applicable.

· **Solubility in / Miscibility with**

water:

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic:

Not determined.

· **Solvent content:**

Organic solvents:

91.3 %

Water:

0.0 %

(Contd. on page 6)



Trade name: 62243 EZCoat Gray

(Contd. of page 5)

VOC (EC)	687.0 g/l
Solids content:	8.7 %
Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
 - Nitrogen oxides
 - Hydrocarbons
 - Carbon monoxide and carbon dioxide

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Repr. 2

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)



Trade name: 62243 EZCoat Gray

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1950
· ADG, IMDG, IATA	
· UN proper shipping name	1950 AEROSOLS
· ADG	AEROSOLS
· IMDG	AEROSOLS, flammable
· IATA	
· Transport hazard class(es)	
· ADG	
· Class	2.5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· Packing group	Void
· ADG, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No

(Contd. on page 8)



Trade name: 62243 EZCoat Gray

(Contd. of page 8)

51274-00-1	YELLOW IRON OXIDE	
1333-86-4	Carbon black	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	
68911-87-5	montmorilontie clay complex	
100-41-4	ethylbenzene	
111-76-2	2-butoxyethanol	
1332-37-2	Iron oxide	
61791-55-7	Amines, N-tallow alkyltrimethylenedi-	
67-56-1	methanol	
147-14-8	Phthalocyanine Blue	
95-63-6	1,2,4-trimethylbenzene	
7727-43-7	barium sulphate, natural	
14807-96-6	Talc	
57-55-6	Methyl glycol	
78-83-1	butanol	
7732-18-5	water	
· Standard for the Uniform Scheduling of Medicines and Poisons		
67-64-1	acetone	S5
108-88-3	toluene	S6
78-93-3	butanone	S5
1330-20-7	xylene	S6
111-76-2	2-butoxyethanol	S6
67-56-1	methanol	S5, S6

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene

· **Hazard statements**

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

(Contd. on page 10)



Trade name: 62243 EZCoat Gray

(Contd. of page 9)

P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a FLAMMABLE AEROSOLS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 *Extremely flammable gas.*
 H225 *Highly flammable liquid and vapour.*
 H226 *Flammable liquid and vapour.*
 H280 *Contains gas under pressure; may explode if heated.*
 H304 *May be fatal if swallowed and enters airways.*
 H315 *Causes skin irritation.*
 H319 *Causes serious eye irritation.*
 H335 *May cause respiratory irritation.*
 H336 *May cause drowsiness or dizziness.*
 H361 *Suspected of damaging fertility or the unborn child.*
 H373 *May cause damage to organs through prolonged or repeated exposure.*

· **Department issuing SDS:** Environmental Protection Department

· **Contact:** 02 9772 9000

· **Abbreviations and acronyms:**

RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
 ICAO: *International Civil Aviation Organisation*
 ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
 IMDG: *International Maritime Code for Dangerous Goods*
 IATA: *International Air Transport Association*
 EINECS: *European Inventory of Existing Commercial Chemical Substances*
 ELINCS: *European List of Notified Chemical Substances*
 CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
 VOC: *Volatile Organic Compounds (USA, EU)*
 LC50: *Lethal concentration, 50 percent*
 LD50: *Lethal dose, 50 percent*
 PBT: *Persistent, Bioaccumulative and Toxic*
 vPvB: *very Persistent and very Bioaccumulative*
 Flam. Gas 1: *Flammable gases – Category 1*
 Aerosol 1: *Aerosols – Category 1*
 Press. Gas C: *Gases under pressure – Compressed gas*
 Flam. Liq. 2: *Flammable liquids – Category 2*
 Flam. Liq. 3: *Flammable liquids – Category 3*
 Skin Irrit. 2: *Skin corrosion/irritation – Category 2*
 Eye Irrit. 2A: *Serious eye damage/eye irritation – Category 2A*
 Repr. 2: *Reproductive toxicity – Category 2*
 STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*
 STOT RE 2: *Specific target organ toxicity (repeated exposure) – Category 2*
 Asp. Tox. 1: *Aspiration hazard – Category 1*