SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

1 Identification

- · Product identifier
- · Trade name: 62223 EZCoat Olive Green
- · Article number: 62223
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc.

1685 Overview Drive Rock Hill, SC 29730

803 207 8225

Sydney Automotive Paints and Equipment Pty Ltd Unit 3A, 366 Edgar Street Condell Park, 2200 NSW, Australia 02 9772 9000 FAX: 02 9772 9001 reception@sape.com.au

· Further information obtainable from:

cust_care@semproducts.com: SEM Products,Inc.: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

· Classification of the substance or mixture



flame

Aerosol 1 H222 Extremely flammable aerosol.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)

(Contd. of page 1)

Printing date 03.10.2017

Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

· Hazard statements

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture: consisting of the following components.

Dangerous o	components:	
67-64-1	acetone	40-60%
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2A, H319; STOT SE 3, H336	
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
	♦ Flam. Gas 1, H220; ♦ Press. Gas C, H280	
108-88-3		10-13%
	♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
78-93-3	butanone	1.5-5%
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2A, H319; STOT SE 3, H336	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5-5%
	♦ Flam. Liq. 3, H226; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	

(Contd. on page 3)

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

	(Cont	d. of page 2)
110-19-0	isobutyl acetate	1.5-5%
	♦ Flam. Liq. 2, H225	
763-69-9	ethyl 3-ethoxypropionate	1-1.5%
	♦ Flam. Liq. 3, H226	
108-65-6	ethyl 3-ethoxypropionate	1-1.5%
	♦ Flam. Liq. 3, H226	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special measures required.

(Contd. on page 4)

Hazchem: 2YE

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 3)

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Control paramet	ers	
· Ingredients with	limit values that require monitoring at the workplace:	
67-64-1 acetone		
WES (Australia)	Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm	
108-88-3 toluene		
WES (Australia)	Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm Sk	
78-93-3 butanon	e	
WES (Australia)	Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm	
110-19-0 isobuty	l acetate	
WES (Australia)	Long-term value: 713 mg/m³, 150 ppm	
108-65-6 2-meth	108-65-6 2-methoxy-1-methylethyl acetate	
WES (Australia)	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 4)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

 $\cdot \textit{Change in condition}$

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 55 °C

• Flash point: $-103 \, ^{\circ}C$

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 465 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 13 Vol %

(Contd. on page 6)

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

	(Contd. of page
· Vapour pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.7528 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	89.5 %
Water:	0.0 %
VOC (EC)	674.1 g/l
Solids content:	10.4 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 7)

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 6)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

147	Transpo.	rt inf	ormat	ion

· UN-Number	
· ADG, IMDG, IATA	UN1950

· UN proper shipping name

· ADG 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 8)

ΑU

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

	(Contd. of page
Transport hazard class(es)	
ADG	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
Packing group ADG, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SWI Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litt
	Category A. For AEROSOLS with a capacity above 1 litt
	Category B. For WASTE AEROSOLS: Category C, Clear living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 lit.
Segregation Code	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capac
	above 1 litre: Segregation as for the appropria
	subdivision of class 2. For WASTE AEROSOL
m	Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of M and the IBC Code	Marpol Not applicable.
Transport/Additional information:	аррисани
ADG Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
~ ~ ~ ~ ~	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	Not permitted as Excepted Quantity (Contd. on page)

SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 8)

· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1
· Hazchem:	2YE

	th and environmental regulations/legislation specific for the substance or mixture	<u> </u>
	nventory of Chemical Substances	
67-64-1		
	Petroleum gases, liquefied, sweetened	
108-88-3		
	butanone	
	4-chloro-alpha,alpha,alpha-trifluorotoluene	
	isobutyl acetate	
763-69-9	ethyl 3-ethoxypropionate	
	2-methoxy-1-methylethyl acetate	
13463-67-7	titanium dioxide	
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	
2807-30-9	2-(propyloxy)ethanol	
51274-00-1	YELLOW IRON OXIDE	
1330-20-7	xylene	
1333-86-4	Carbon black	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	
	montmorilontie clay complex	
	ethylbenzene	
61791-55-7	Amines, N-tallow alkyltrimethylenedi-	
	methanol	
14302-13-7	PHTHALO GREEN PIGMENT	
95-63-6	1,2,4-trimethylbenzene	
	2-methoxypropyl acetate	
	silicon dioxide, chemically prepared	
78-83-1		
57-55-6	Methyl glycol	
7732-18-5		
	r the Uniform Scheduling of Medicines and Poisons	
67-64-1 d		<i>S</i> 5
108-88-3		S6
		S5
78-93-3 l		
1330-20-7	*	S6
67-56-1 1	netnanol	S5, S

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). (Contd. on page 10)

ÁΙ

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 9)

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

· Hazard statements

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 11)

neet SEM

Printing date 03.10.2017 Version number 18 Revision: 03.10.2017

Trade name: 62223 EZCoat Olive Green

(Contd. of page 10)

· Department issuing SDS: Environmental Protection Department

· Contact: 02 9772 9000

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

ΔIJ