SEM

Printing date 03.10.2017

Version number 6

1 Identification

- · Product identifier
- · Trade name: 39322 Instabond Accelerator
- · Article number: 39322
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

> Sydney Automotive Paints and Equipment Pty Ltd Unit 3A, 366 Edgar Street Condell Park, 2200 NSW, Australia 02 9772 9000 FAX: 02 9772 9001 reception@sape.com.au

· Further information obtainable from:

cust_care@semproducts.com: SEM Products,Inc.: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: Poison Information Centre Call 13 11 26 (Australia)

2 Hazard(s) Identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

 (Contd. on page 2)

Revision: 03.10.2017

_/

(Contd. of page 1)

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labelling:

heptane

N,*N*-dimethyl-p-toluidine

· Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture: consisting of the following components.

· Dangerous compone	nts:	
---------------------	------	--

142-82-5 heptane 40-60% 🚸 Flam. Liq. 2, H225; 🕹 Asp. Tox. 1, H304; 伙 Skin Irrit. 2, H315; STOT SE 3, H336 67-64-1 acetone 40-60% **♦** Flam. Liq. 2, H225; **♦** Eye Irrit. 2A, H319; STOT SE 3, H336

· Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

SEM

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

(Contd. of page 2)

Hazchem: •3YE

4 First Aid Measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

SEM

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

142-82-5 heptane

WES (Australia) Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm

67-64-1 acetone

WES (Australia) Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

SEM

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

Physical and Chemical Propertie	es .
Information on basic physical and chen	nical properties
General Information	
Appearance:	
Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 55 °C
Flash point:	-18 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	215 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	233 hPa
Density at 20 °C:	0.72631 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	99.2 %

(Contd. on page 6)

SEM

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

(Contd. of page 5)

Solids content: 0.0 %

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

ΑT

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · ADG, IMDG, IATA	UN1993	
· UN proper shipping name · ADG	1993 FLAMMABLE LIQUID, N. O.S. (ACETONE HEPTANES), ENVIRONMENTALLY HAZARDOUS, specia provision 640D	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE, HEPTANES)	
· Transport hazard class(es)		
· ADG, IMDG		

· Class	3 Flammable liquids.	
· Label	3	
Class		
· Class · Label	3 Flammable liquids. 3	
	3	
· Packing group · ADG, IMDG, IATA	II	
· Environmental hazards:	Product contains environmentally hazardous substances: heptane	
· Marine pollutant:	Yes Symbol (fish and tree)	
· Special marking (ADG):	Symbol (fish and tree)	
· Special precautions for user	Warning: Flammable liquids.	
· EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	B	
· Transport in bulk according to Annex I and the IBC Code	I of Marpol Not applicable.	
ana me IDC Coae	пон аррисавие.	

(Contd. on page 8)

SEM

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

	(Contd. of page
Transport/Additional information:	
· ADG	
Limited quantities (LQ)	1L
\cdot Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIA
	PROVISION 640D (ACETONE, HEPTANES), 3, 1
	ENVIRONMENTALLY HAZARDOUS
Hazchem:	•3YE

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

67-64-1 acetone

S5

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

- · Signal word Danger
- · Hazard-determining components of labelling:

heptane

N,*N*-dimethyl-p-toluidine

· Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

(Contd. on page 9)

Printing date 03.10.2017 Version number 6 Revision: 03.10.2017

Trade name: 39322 Instabond Accelerator

(Contd. of page 8)

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Environmental Protection Department
- · Contact: 02 9772 9000
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1