

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CAM Ultra Fine Glazing Putty
Product code : CUPS2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Body filler/stopper
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de

Telephone : 04122 717 0
Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0
sds@vosschemie.de

1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

IMPORTED BY:

Sydney Automotive Paints & Equipment PTY LTD Unit A3, 366 Edgar St. Condell Park NSW 2200 AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001

Emergency telephone number: If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zealand 0800 764 766

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust / mist / vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

styrene

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
contains
Resin

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3;	>= 10 - < 20

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	H412	>= 10 - < 20
		Acute toxicity estimate Acute inhalation toxicity (vapor): 11,8 mg/l Carc. 2; H351	
1,4-naphthoquinone	130-15-4 204-977-6 01-2120760462-57	Acute Tox. 3; H301 Acute Tox. 1; H330 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>=0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
		Acute toxicity estimate Acute oral toxicity: 124 mg/kg Acute inhalation toxicity (dust/mist): 0,046 mg/l	
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9		>= 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

- Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
Keep under medical supervision for at least 48 hours.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
Sweep up to prevent slipping hazard.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

- Environmental precautions : Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.
Avoid contact with skin and eyes.
Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture.
Avoid inhalation of dust from sanding.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight. Do not store at temperatures above 30 °C / 86 °F.

Advice on common storage : Incompatible with oxidizing agents.
Keep away from food and drink.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit category: 2;(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit category: 2;(II)				
Further information: When there is compliance with the OEL and biological				

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

	tolerance values, there is no risk of harming the unborn child			
		TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
styrene	100-42-5	AGW	20 ppm 86 mg/m ³	DE TRGS 900
Peak-limit category: 2:(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
Peak-limit category: 2:(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
Peak-limit category: 2:(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
Barium sulphate	7727-43-7	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit category: 2:(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit category: 2:(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g Creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
styrene	Workers	Dermal	Long-term systemic effects, Chronic effects	406 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects, Chronic effects	85 mg/m ³
	Workers	Inhalation	Acute systemic effects, Chronic effects	289 mg/m ³
	Workers	Inhalation	Acute local effects,	306 mg/m ³

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

			Short-term exposure	
	Consumers	Oral	Long-term systemic effects, Chronic effects	2,1 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects, Chronic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Chronic effects	10,0 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Short-term exposure	174,25 mg/m ³
	Consumers	Inhalation	Acute local effects, Short-term exposure	182,75 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
styrene	Fresh water	0,028 mg/l
	Sea water	0,014 mg/l
	Fresh water sediment	0,614 mg/kg dry weight (d.w.)
	Sea sediment	0,307 mg/kg dry weight (d.w.)
	Soil	0,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	5 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : >= 0,4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Butyl gloves are not suitable. Nitrile gloves are not suitable. Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Color : white

Odor : characteristic

Melting point/range : -30 °C
Literary value styrene

Boiling point/boiling range : 145 °C (1.013 hPa)
Literary value styrene

Upper explosion limit / Upper flammability limit : 6,1 %(V)
Literary value styrene

Lower explosion limit / Lower flammability limit : 1,1 %(V)
Literary value styrene

Flash point : 31 °C(1.013 hPa)
Literary value styrene

Autoignition temperature : 490 °C (1.013 hPa)
Literary value styrene

pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Viscosity, dynamic : not determined
Viscosity, kinematic : not determined
Solubility(ies)
Water solubility : 0,32 g/l (25 °C)
Literary value styrene
Partition coefficient: n-
octanol/water : No data available
Vapor pressure : 6,67 hPa (20 °C)
Literary value styrene
Density : 1,8 g/cm³ (20 °C)

9.2 Other information

Explosives : Not explosive
In use, may form flammable/explosive vapor-air mixture.
Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Avoid radical-forming starting agents, peroxides and reactive metals.
Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents
polymerization initiators
Copper
Copper alloys
Brass

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

styrene:

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute toxicity estimate: 11,8 mg/l
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Titanium dioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LD50 (Rat): > 6,8 mg/l
Exposure time: 4 h

1,4-naphthoquinone:

Acute oral toxicity : LD50 Oral (Rat): 124 mg/kg
Acute toxicity estimate: 124 mg/kg
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 0,046 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Acute toxicity estimate: 0,046 mg/l

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity
Effects of skin contacts may include:
Causes burns.

Talc:

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

styrene:

Species : Rabbit
Result : irritating

Titanium dioxide:

Remarks : No skin irritation

1,4-naphthoquinone:

Result : Causes burns.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

styrene:

Species : Rabbit
Result : irritating

Titanium dioxide:

Remarks : Dust contact with the eyes can lead to mechanical irritation.

1,4-naphthoquinone:

Result : Risk of serious damage to eyes.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Respiratory sensitization

Not classified based on available information.

Components:

styrene:

Species : Guinea pig
Result : Does not cause skin sensitization.

Titanium dioxide:

Remarks : No known sensitising effect.

1,4-naphthoquinone:

Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

styrene:

Reproductive toxicity – Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Components:

styrene:

Assessment : May cause respiratory irritation.

1,4-naphthoquinone:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

Components:

styrene:

Routes of exposure : Inhalation
Target Organs : hearing organs

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

styrene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,02 mg/l Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 4,9 mg/l Exposure time: 72 h

EC10 (Selenastrum capricornutum (green algae)): 0,28 mg/l Exposure time: 96 h

Toxicity to microorganisms : EC50 (Natural microorganism): ca. 500 mg/l Method: OECD Test Guideline 209

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,01 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Titanium dioxide:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h

1,4-naphthoquinone:

Toxicity to fish : (Oryzias latipes (Japanese medaka)): 0,045 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,0261 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 0,42 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

styrene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70,9 %
Exposure time: 28 d

1,4-naphthoquinone:

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

12.3 Bioaccumulative potential

Components:

styrene:

Partition coefficient: n-octanol/water : log Pow: 2,96 (25 °C)

1,4-naphthoquinone:

Partition coefficient: n-octanol/water : log Pow: 1,77 (25 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Dispose of in accordance with local regulations. Dispose of wastes in an approved waste disposal facility. Send to a licensed waste management company.

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
07 02 08, other still bottoms and reaction residues

SECTION 14: Transport information

14.1 UN number or ID number

ADG : UN 1866
ADN : UN 1866
ADR : UN 1866
RID : UN 1866
IMDG : UN 1866
IATA : UN 1866

14.2 UN proper shipping name

ADG : RESIN SOLUTION
ADN : RESIN SOLUTION
ADR : RESIN SOLUTION
RID : RESIN SOLUTION
IMDG : RESIN SOLUTION
IATA : Resin solution

14.3 Transport hazard class(es)

ADG : 3
ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30

CAM Ultra Fine Glazing Putty

Version		Revision Date:	Date of last issue: -
1.0AUS	DE / EN	30.01.2023	Date of first issue: 01.07.2022

Labels	: 3
ADG	: III
ADR	
Packing group	: III

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADG / ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : No

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 250 g/l
VOC content for the product in a ready to use condition.

Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product. **AICIS:** All of the significant ingredients in this formulation are compliant with AICIS regulations.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.
H301 : Toxic if swallowed.
H304 : May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Ultra Fine Glazing Putty

Version	Revision Date:	Date of last issue: -
1.0AUS DE / EN	30.01.2023	Date of first issue: 01.07.2022

- H314 : Causes severe skin burns and eye damage.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H330 : Fatal if inhaled.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H351 : Suspected of causing cancer if inhaled.
- H361d : Suspected of damaging the unborn child.
- H372 : Causes damage to organs through prolonged or repeated exposure.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Aquatic Acute : Short-term (acute) aquatic hazard
- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Asp. Tox. : Aspiration hazard
- Carc. : Carcinogenicity
- Eye Dam. : Serious eye damage
- Eye Irrit. : Eye irritation
- Flam. Liq. : Flammable liquids
- Repr. : Reproductive toxicity
- Skin Corr. : Skin corrosion
- Skin Irrit. : Skin irritation
- Skin Sens. : Skin sensitization
- STOT RE : Specific target organ toxicity - repeated exposure
- STOT SE : Specific target organ toxicity - single exposure
- 2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
- DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
- TRGS 903 : c - Biological limit values
- 2004/37/EC / TWA : Long term exposure limit
- DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China;

CAM Ultra Fine Glazing Putty

Version 1.0AUS DE / EN Revision Date: 30.01.2023 Date of last issue: -
Date of first issue: 01.07.2022

IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Repr. 2	H361d
STOT RE 1	H372

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN