



SPECIFICATIONS

LIFTING CAPACITY	3,2 t
LIFTING HEIGHT	≤ 1000 mm
PLATFORM LENGTH	1500–2070 mm
PLATFORM WIDTH	520 mm
OVERALL WIDTH	1898 mm
OVERALL HEIGHT (CLOSED)	110 mm
HYDRAULIC PRESSURE	25 MPa
LIFTING TIME	< 45 s
POWER SUPPLY	2,2 kW
NET WEIGHT	~ 600 kg

Double Scissor Lift h1000 mm

- Precision Leveling System**
 Advanced design for quick and accurate adjustment.
- Integrated Safety Solutions**
 Independent dual hydraulic circuit with anti-explosion valves, safety photocell, active buzzer during lowering, and time relay for controlled descent sequence.
- Ultra-Low Profile**
 Resting height: 110 mm, maximum lifting height: ≤ 1000 mm.
- Extendable Platform**
 Length: 1500 mm, extendable up to 2070 mm; platform width: 520 mm each.
- Versatile Installation**
 The lift can be installed either above ground or flush-mounted (in-ground), offering maximum flexibility and optimal integration into the workspace.
- Robust Structure**
 Double-scissor mechanism with reinforced base and synchronized arms for smooth and uniform movement.
- Dual-Circuit Technology**
 Ensures stability and operational safety even in the event of a circuit failure.

Ideal for inspections, general maintenance, and control operations in professional body shops.

